

Article Number: 855-14200



Connector, Fiber Optic LC Multimode 900um (Beige) Simplex (BTW) - Epoxy & Polish Description:

Base Data		
	Local Order Number	FCLC
	Туре	FCLC
	Color	Beige (BGE)
	Features and Benefits	 Use with epoxy or anaerobic adhesives for different applications or user preference. Pre-radiused zirconia ceramic ferrules provide precision installation. Meet ANSI/TIA/EIA 568-C standards. Meet ANSI/TIA/EIA 604 (FOCIS) connector interface requirements.
	Quantity Per	bag
	Product Description	Our epoxy/anaerobic connectors are designed for field or factory installation, using either epoxy or anaerobic adhesives. These connectors are made with pre-radiused zirconia ceramic ferrules to provide precision alignment and installation. Epoxy adhesives provide affordable and reliable connections with lowest losses (less than 0.5dB). The epoxy can be allowed to set overnight or cured in an inexpensive oven. Anaerobic adhesives can be used with accelerators for faster curing
	Technical Description	LC Multimode Fiber Connector, Beige
	Short Description	Connector, Fiber Optic LC Multimode 900um (Beige) Simplex (BTW) - Epoxy & Polish
Logistic and Packaging		
	Package Quantity (Imperial)	10
	Package Quantity (Metric)	1
	Customs Number(Schedule B)	8536700000

generated on: 2/3/2017



generated on: 2/3/2017