



PRODUCT DATASHEET

Barbara series

last update 11/9/2015


DETAILS

Product Number	FCN13926_BARBARA-W-PF-VERO10
Family	Barbara
Type	RefPack
Color	metal
Diameter	70 mm
Height	41,7 mm
Style	round
Optic Material	PC
Holder Material	
Fastening	
Status	production ready
ROHS Comliant	Yes
Date Updated	11/09/2015




OPTICAL PROPERTIES


LED	Viewing Angle	Light Beam	Effi- ciency	cd/lm	Connector
VERO10	31 deg	Wide	91 %	2.300	-



INDEX	PART NO	MATERIAL	COLOUR
1	Socket	PC	White
2	Reflector	PC	Metal


Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: class C According to DIN ISO 2768-2 Form and position: class L		LEDiL Ledil Oy Salorankatu 10 FIN 24240 SALO Finland	
THIRD ANGLE PROJECTION: 		DRAWING TITLE DATA SHEET BARBARA-PF-SOCKET-VER010	
This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy.		SIZE A3	PART NUMBER -
		SCALE 1:1	WEIGHT - SHEET 1/1

Luminaire: LEDiL Oy FCN13926_BARBARA-W-PF-VERO10
Lamps: 1 x VERO10_(BXRC-30E1000B)_672.286lm@250mA_CCT=3000K_P=6.33971W_I=249.9mA



Luminaire: LEDiL Oy FCN13926_BARBARA-W-PF-VERO10

Lamps: 1 x VERO10_(BXRC-30E1000B)_672.286lm@250mA_CCT=3000K_P=6.33971W_I=249.9mA



NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.

GENERAL INFORMATION

- Product series especially designed & optimized for series of LEDs.
- Special care taken to make light distribution as uniform as possible.

Note! Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.