




## Glass Passivated Ultrafast Rectifier

Patented\*



GP20

\*Glass Encapsulation technique is covered by Patent No. 3,996,602, brazed-lead assembly to Patent No. 3,930,306

### FEATURES

- Cavity-free glass-passivated junction
- Ultrafast reverse recovery time
- Low forward voltage drop
- Low leakage current
- Low switching losses, high efficiency
- High forward surge capability
- Meets environmental standard MIL-S-19500
- Solder dip 260 °C, 40 s
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC

RoHS  
COMPLIANT

### TYPICAL APPLICATIONS

For use in high frequency rectification and freewheeling application in switching mode converters and inverters for consumer, computer, automotive and telecommunication.

### MECHANICAL DATA

**Case:** GP20, molded epoxy over glass body

Epoxy meets UL 94V-0 flammability rating

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD22-B102

E3 suffix for consumer grade, meets JESD 201 class 1A whisker test, HE3 suffix for high reliability grade (AEC Q101 qualified), meets JESD 201 class 2 whisker test

**Polarity:** Color band denotes cathode end

PRIMARY CHARACTERISTICS	
$I_{F(AV)}$	5.0 A
$V_{RRM}$	100 V to 200 V
$I_{FSM}$	135 A
$t_{rr}$	35 ns
$V_F$	0.95 V
$I_R$	5.0 $\mu$ A
$T_J$ max.	175 °C

MAXIMUM RATINGS ( $T_A = 25$ °C unless otherwise noted)					
PARAMETER	SYMBOL	FGP50B	FGP50C	FGP50D	UNIT
Maximum repetitive peak reverse voltage	$V_{RRM}$	100	150	200	V
Maximum RMS voltage	$V_{RMS}$	70	105	140	V
Maximum DC blocking voltage	$V_{DC}$	100	150	200	V
Maximum average forward rectified current 0.375" (9.5 mm) lead length (Fig. 1)	$I_{F(AV)}$	5.0			A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	$I_{FSM}$	135			A
Operating junction and storage temperature range	$T_J, T_{STG}$	- 65 to + 175			°C

## FGP50B thru FGP50D

Vishay General Semiconductor

**ELECTRICAL CHARACTERISTICS** ( $T_A = 25^\circ\text{C}$  unless otherwise noted)

PARAMETER	TEST CONDITIONS	SYMBOL	FGP50B	FGP50C	FGP50D	UNIT
Maximum instantaneous forward voltage <sup>(1)</sup>	5.0 A	$V_F$		0.95		V
Maximum DC reverse current at rated DC blocking voltage	$T_A = 25^\circ\text{C}$ $T_A = 100^\circ\text{C}$	$I_R$		5.0 50		$\mu\text{A}$
Maximum reverse recovery time	$I_F = 0.5 \text{ A}$ , $I_R = 1.0 \text{ A}$ , $I_{rr} = 0.25 \text{ A}$	$t_{rr}$		35		ns
Typical junction capacitance	4.0 V, 1 MHz	$C_J$		100		pF

## Note:

(1) Pulse test: 300  $\mu\text{s}$  pulse width, 1 % duty cycle**THERMAL CHARACTERISTICS** ( $T_A = 25^\circ\text{C}$  unless otherwise noted)

PARAMETER	SYMBOL	FGP50B	FGP50C	FGP50D	UNIT
Typical thermal resistance <sup>(1,2)</sup>	$R_{0JA}$ $R_{0JL}$		60 20		$^\circ\text{C}/\text{W}$

## Notes:

(1) Thermal resistance from junction to lead at 0.375" (9.5 mm) lead length with both leads attached to heatsinks.

(2) Thermal resistance from junction to ambient at 0.375" (9.5 mm) lead length and mounted on P.C.B..

**ORDERING INFORMATION** (Example)

PREFERRED P/N	UNIT WEIGHT (g)	PREFERRED PACKAGE CODE	BASE QUANTITY	DELIVERY MODE
FGP50D-E3/54	1.01	54	1400	13" diameter paper tape and reel
FGP50D-E3/73	1.01	73	2000	Ammo pack packaging
FGP50DHE3/54 <sup>(1)</sup>	1.01	54	1400	13" diameter paper tape and reel
FGP50DHE3/73 <sup>(1)</sup>	1.01	73	2000	Ammo pack packaging

## Note:

(1) Automotive grade AEC Q101 qualified


**RATINGS AND CHARACTERISTICS CURVES**( $T_A = 25^\circ\text{C}$  unless otherwise noted)

Figure 1. Maximum Forward Current Derating Curve




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current




Figure 3. Typical Instantaneous Forward Characteristics




Figure 5. Typical Junction Capacitance





Figure 4. Typical Reverse Leakage Characteristics

#### PACKAGE OUTLINE DIMENSIONS in inches (millimeters)



### Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Vishay](#):

[FGP50B-E3/54](#) [FGP50B-E3/73](#) [FGP50BHE3/54](#) [FGP50BHE3/73](#) [FGP50C-E3/54](#) [FGP50C-E3/73](#) [FGP50CHE3/54](#)  
[FGP50CHE3/73](#) [FGP50D-E3/54](#) [FGP50D-E3/73](#) [FGP50DHE3/54](#) [FGP50DHE3/73](#)