

Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Catalog Cut Sheet
 - PDF-LC Fiber Opt ..
 - Part Drawings
 - DXF-LC Simplex C ..
 - PDF-LC Conn. 3.0 ..
 - DWG-LC Simplex C ..
 - Specification Sheets
 - PDF-LC Fiber Opt ..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor
- Install & Maintain
 - Installation Instructions
 - PDF-LC Fiber Opt ..
 - Stripping Templates
 - PDF-LC Fiber Opt ..

Home > Product On-Line Catalog > Search Results >

Current refinements (click to remove) Search Tips [?](#)

Text Search: 'FLCSS3.0BU'

Your search criteria matched only one product, shown below

FLCSS3.0BU



- TIA/EIA-604 FOCIS-10 compatible connectors
- Exceed TIA/EIA-568-B.3 requirements
- Insertion loss: 0.10dB average (multimode and singlemode)
- Return loss: >20dB (multimode), >40dB (singlemode)
- Non-optical disconnect maintains data transmission under tensile loads for jacketed cable
- Each simplex connector includes the following: one connector body/ferrule assembly, one crimp sleeve, one dust cap, and depending on the part number ordered, one boot for 900µ m buffered fiber and one boot for 1.6mm– 2.0mm jacketed cable or one boot for 3.0mm jacketed cable
- Each duplex connector includes two connector body/ferrule assemblies, two crimp sleeves, two dust caps, one duplex clip, and depending on the part number ordered, two boots for 1.6mm - 2.0mm jacketed cable, two boot for 3.0mm jacketed cable, or two boots for 900µ m buffered fiber
- LC duplex clip available separately for duplexing two simplex Panduit LC Connectors
- Fiber cable type: tight-buffered recommended
- Fiber cable size: accept 1.6mm – 2.0mm or 3.0mm jacketed cable, 900µm buffered fiber (noted in part description)
- For 250µm coated fiber termination, use 250 micron fiber build-up tube kit or fan-out kits
- Ferrule type: 1.25mm zirconia ceramic (highest durability for repeated matings)
- Field polish termination – Panduit recommends anaerobic adhesive
- Use field polish termination kit (FIELDKIT)

▪ Part Number	FLCSS3.0BU
▪ RoHS Compliancy Status	RoHS directive is not applicable
▪ Note	Intended for use in fixed installations which are outside the scope of RoHS
▪ Part Description	LC singlemode simplex fiber optic connector for 3.0mm jacketed cable installation.
▪ Product Type	LC Simplex Connector
▪ Color	Blue
▪ Fiber Compatibility	9/125µm
▪ Fiber Cable Size	3.0mm
▪ Fiber Cable Type	Tight-buffered recommended
▪ Fiber Type	Singlemode
▪ Termination Style	Field Polish
▪ CE Compliant	No
▪ Ferrule Type	Zirconia Ceramic
▪ Pricing Description	LC Simpl Singlemode Fiber Optic Connector - Field Polish
▪ Min. Order UOM	PC
▪ Min. Order Qty.	1
▪ BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
▪ Add to Favorite Product List	<input type="checkbox"/>

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.