

REVISIONS				
REV	ECN	DESCRIPTION	DATE	APPROVED
T		ELASTOMER GASKET OPTION ADDED	SEP 15/09	ZLJ
U		DETAIL H ADDED	JAN 14/10	ZLJ
V		NOTE #3 ADDED	JAN 13/11	ZLJ
Z		BOTTOM VIEW ADDED	NOV 22/12	ZLJ

FS1-SF1-1XXX

MOUNTING SCREW OPTION

- 1 = 8 mm MOUNTING SCREW SHIPPED BULK IN SAME TRAYS WITH CAGE ASSEMBLIES
2 = NO MOUNTING SCREW SUPPLIED
3 = 10 mm MOUNTING SCREW WITH LOCK WASHER SHIPPED BULK IN SAME TRAYS WITH CAGE ASSEMBLIES


GASKET OPTION

- E = STAINLESS STEEL EMI GASKET
F = FOAM, CHOMERICS SOFT SHIELD 4800, EMI GASKET
C = CONDUCTIVE ELASTOMER, CHOMERICS S6305


KEYING OPTION (SEE BELOW TABLE FOR FURTHER CLARIFICATION)

- 0 = NO KEY
1 = KEY #1
2 = KEY #2
3 = KEY #3
4 = KEY #4
5 = KEY #5
6 = KEY #6
7 = KEY #7
24 = KEY #2 AND #4
46 = KEY #4 AND #6


Key Option	Part Number	Description
0	FS1-SF1-10XX	No Key
1	FS1-SF1-11XX	SATA 'X' Cable
2	FS1-SF1-12XX	
3	FS1-SF1-13XX	
4	FS1-SF1-14XX	SAS Universal Port
5	FS1-SF1-15XX	
6	FS1-SF1-16XX	
7	FS1-SF1-17XX	SATA 'M' Cable
2, 4	FS1-SF1-124XX	SAS Out Port
4, 6	FS1-SF1-146XX	SAS In Port



PART NUMBER: **FS1-SF1-14C1** SHOWN
(CAGE ASSEMBLY WITH ELASTOMERIC GASKET
AND 8mm MOUNTING SCREWS SHIPPED BULK)



PART NUMBER: **FS1-SF1-14E1** SHOWN
(CAGE ASSEMBLY WITH STAINLESS STEEL
GASKET AND 8mm MOUNTING SCREWS SHIPPED BULK)








PART NUMBER: **FS1-SF1-14F1** SHOWN
(CAGE ASSEMBLY WITH FOAM GASKET
AND 8mm MOUNTING SCREWS SHIPPED BULK)



DO NOT SCALE DRAWING

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE
OR USED FOR MANUFACTURING PURPOSES WITHOUT PERMISSION FROM AMPHENOL CANADA CORP.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE: DECIMALS ANGLES .X ± 0.25 ± 2° .XX ± 0.10 .XXX ± 0.05 MATERIAL AND FINISH		APPROVALS		DATE	Amphenol Canada Corp.	
		DRAWN	ZLJ	JAN 6/09	TITLE	
DWG. REL. NO. EAR 123XX		DESIGNED	ZLJ	JAN 06/09	MINI SAS 0 DEGREE SINGLE PORT CAGE	
CODE IDENT. NO. 03554		CHECKED			REV. Z	
		QA APP'D			P-FS1-SF1-1XXX	
		ENG. APP'D			SHEET 1 OF 1	
		DWG. APP'D			SCALE NTS	
					PROJECT SFF	



KEY #1


KEY #2

KEY #3


KEY #5

KEY #6


KEY #7







KEY #2, 4




KEY #4, 6




RECOMMENDED PANEL CUT-OUT

RECOMMENDED FACE PLATE TO
LOCATING POST DISTANCE

DETAIL H
SCALE 16 : 1



DETAIL G
SCALE 4 : 1



DO NOT SCALE DRAWING

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT PERMISSION FROM AMPHENOL CANADA CORP.



REVISIONS				
REV.	ECN	DESCRIPTION	DATE	APPROVE
Z		SEE SHEET 1	FEB 22/12	ZLJ

NOTES:

1) MATERIAL:

MAIN CAGE: ZINC DIECAST SHELL WITH 150 MICROINCHES OF
NICKEL PLATING
EMC GASKET: SEE SHEET 1
COVER: STAINLESS STEEL
MOUNTING SCREW: AISI 1010 STEEL

2) ROHS COMPLIANT

3) COMPATIBLE WITH SFF-8088 SHIELDED MULTILANE MINI SAS PLUGS

(UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE: DECIMAL ANGLES X ± 0.25 XX ± 0.10 XXX ± 0.05 MATERIAL AND FINISH	APPROVALS		DATE		Amphenol Canada Corp.	
	DESIGNED BY	JLJ	JAN 06/09	DATE		
	DESIGNED BY	JLJ	JAN 06/09			
	CHECKED					
	QA APPO					
MINI SAS 0 DEGREE SINGLE PORT CAGE						
ENG REL NO EAR 123XX	E APPO	C	DWG. NO. P-F51-SF1-1XXX	REV. 1		
CODE IDENT NO 03554	ENG APPO	SCALE NTS	PROG SFF	SHEET 1	OF 1	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[FS1-SF1-14E1](#)