

Search Results

- Evaluate
- FAQ's
- Design a Solution
- Specification Sheets
- PDF-Ferrules wit ..
- How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips 

 Text Search: 'FSDX77-8-D'

Your search criteria matched only one product, shown below

FSDX77-8-D



- Expanded sleeve inside diameter for wire with thicker insulation
- Meets DIN dimensional and color standards for single wire containment
- Funnel entry for faster insertion and lower installed cost
- Designed with a seamless barrel to contain loose wire strands for superior terminations
- Eases insertion of stranded wire into terminal blocks
- Multiple pin lengths available

▪ Part Number	FSDX77-8-D
▪ RoHS Compliancy Status	Compliant
▪ Part Description	Polypropylene insulated ferrules – single wire DIN expanded end sleeve.
▪ Color	Red
▪ Length (In.)	0.57
▪ Length (mm)	14.5
▪ CE Compliant	No
▪ Inside Diameter (In.)	0.06
▪ Inside Diameter (mm)	1.5
▪ Insulation	Polypropylene
▪ Max. Wire Insul. Dia. (In.)	0.14
▪ Outside Diameter (In.)	0.07
▪ Outside Diameter (mm)	1.8
▪ Pin Length (In.)	0.32
▪ Pin Length (mm)	8.0
▪ Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)
▪ Tool	CT-1002, CT-1003, CT-1123
▪ Wire Range	18 AWG
▪ Wire Range (mm²)	1.00
▪ Wire Strip Length (In.)	15/32
▪ Wire Strip Length (mm)	11.9
▪ Min. Order UOM	PC
▪ Min. Order Qty.	500
▪ BOM Qty. (# of Pkgs.)	
▪ Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

