





SPADE TONGUE TERMINAL *Non-insulated*




Applicable Wire mm ² (AWG#)	Stud Size Metric	Part No.	Nominal Size	Dimensions mm (in.)							Tool No.	Qty/box
				ød ₂	ød ₃	r	ℓ	a	ø d ₁	s		
0.1 to 0.5 (26 to 22)	3	GS3-0.5C		3.2 (.126)	5.0 (.197)	5.0 (.197)	10.0 (.394)	4.0 (.157)	1.0 (.039)	0.5 (.020)	—	2,000
0.25 to 1.5 (22 to 16)	3	GS3-1C		3.2 (.126)	6.0 (.236)	4.5 (.177)	11.0 (.433)	5.0 (.197)	1.6 (.063)	0.8 (.031)	JCH-10	2,000
	3	GS3L-1C		3.2 (.126)	6.5 (.256)	3.5 (.138)	8.0 (.315)	4.0 (.157)				
	3.5	GS3.5-1C		3.7 (.146)	6.0 (.236)	4.5 (.177)	11.0 (.433)	5.0 (.197)				
	3.5	GS3.5L-1C		3.7 (.146)	6.5 (.256)	3.5 (.138)	8.0 (.315)	4.0 (.157)				
	4	GS4M-1C		4.3 (.169)	6.8 (.268)	5.5 (.217)	11.0 (.433)	5.0 (.197)				
	4	GS4-1C		4.3 (.169)	8.0 (.315)	6.0 (.236)	12.0 (.472)	5.0 (.197)				
	5	GS5-1C		5.3 (.209)	10.0 (.394)	6.5 (.256)	13.0 (.512)	5.0 (.197)				
	6	GS6-1C		6.5 (.256)	12.0 (.472)	10.0 (.394)	17.0 (.669)	5.0 (.197)				1,000
	8	GS8-1C		8.4 (.331)	12.0 (.472)	10.0 (.394)	17.0 (.669)	5.0 (.197)				
>2.5 to 6 (12 to 10)	3	GS3-2.5C		3.2 (.126)	6.0 (.236)	4.5 (.177)	11.0 (.433)	5.0 (.197)	2.3 (.091)	0.8 (.031)	JCH-10	2,000
	3.5	GS3.5L-2.5C		3.7 (.146)	6.8 (.268)	4.5 (.177)	11.0 (.433)					
	4	GS4S-2.5C		4.3 (.169)	6.8 (.268)	4.5 (.177)	11.0 (.433)					
	4	GS4-2.5C		4.3 (.169)	8.0 (.315)	6.0 (.236)	12.0 (.472)					
	5	GS5-2.5C		5.3 (.209)	10.0 (.394)	6.5 (.256)	14.0 (.551)					
	6	GS6-2.5C		6.5 (.256)	11.0 (.433)	7.5 (.295)	16.0 (.630)					
>2.5 to 6 (12 to 10)	4	GS4-6C		4.3 (.169)	8.0 (.315)	6.0 (.236)	14.0 (.551)	6.0 (.236)	3.6 (.142)	1.0 (.039)	JCH-10	1,000
	5	GS5-6C		5.3 (.209)	10.0 (.394)	6.5 (.256)	15.0 (.591)					
	6	GS6-6C		6.5 (.256)	11.0 (.433)	7.5 (.295)	16.0 (.630)					
	8	GS8-6C		8.4 (.331)	14.0 (.551)	10.0 (.394)	19.0 (.748)					
>6 to 10 (8)	4	GS4-10C		4.3 (.169)	10.0 (.394)	6.5 (.256)	16.0 (.630)	8.0 (.315)	4.5 (.177)	1.1 (.043)	JCS-350 YH-540	1,000
	5	GS5-10C		5.3 (.209)	10.0 (.394)	6.5 (.256)	16.0 (.630)					
	6	GS6-10C		6.5 (.256)	11.0 (.433)	7.5 (.295)	17.0 (.669)					

Note: 1) Contact J.S.T. Europe N.V., Belgium for the above tools.

2) Delivery lead times may vary depending on the product. Contact JST for details.

SPADE TONGUE TERMINAL *Insulated*



Vinyl-insulated

Applicable Wire mm ² (AWG#)	Stud Size Metric	Part No.	Nominal Size	Dimensions mm (in.)									Color	Tool No.	Qty/box
				ød ₂	ød ₃	r	l ₁	l ₂	a	ø d ₁	ø d ₄	s			
0.25 to 1.5 (22 to 16)	3.5	FVGS3.5-1C		3.7 (.146)	6.0 (.236)	4.5 (.177)		16.0 (.630)					Red	JCH-1112	1,000
	4	FVGS4-1C		4.3 (.169)	8.0 (.315)	6.0 (.236)		17.0 (.669)							
	4	FVGS4M-1C		4.3 (.169)	6.8 (.268)	5.5 (.217)	10.0	16.0 (.630)	5.0	1.6	3.4	0.8			
	5	FVGS5-1C		5.3 (.209)	10.0 (.394)	6.5 (.256)	(.394)	18.0 (.709)	(.197)	(.063)	(.134)	(.031)			
	6	FVGS6-1C		6.5 (.256)	12.0 (.472)	10.0 (.394)		22.0 (.866)							
	8	FVGS8-1C		8.4 (.331)	12.0 (.472)	10.0 (.394)		22.0 (.866)							
>1 to 2.6 (16 to 14)	3	FVGS3-2.5C		3.2 (.126)	6.0 (.236)	4.5 (.177)		17.0 (.669)					Blue	JCH-1112 JCH-1213	1,000
	3.5	FVGS3.5L-2.5C		3.7 (.146)	6.8 (.268)	4.5 (.177)		17.0 (.669)							
	4	FVGS4S-2.5C		4.3 (.169)	6.8 (.268)	4.5 (.177)	11.0	17.0 (.669)	5.0	2.3	4.3	0.8			
	4	FVGS4-2.5C		4.3 (.169)	8.0 (.315)	6.0 (.236)	(.433)	18.0 (.709)	(.197)	(.091)	(.169)	(.031)			
	5	FVGS5-2.5C		5.3 (.209)	10.0 (.394)	6.5 (.256)		20.0 (.787)							
	6	FVGS6-2.5C		6.5 (.256)	11.0 (.433)	7.5 (.295)		22.0 (.866)							
>2.5 to 6 (12 to 10)	4	FVGS4-6C		4.3 (.169)	8.0 (.315)	6.0 (.236)	12.0	20.0 (.787)	6.0	3.6	6.4	1.0	Yellow	JCH-1213	500
	5	FVGS5-6C		5.3 (.209)	10.0 (.394)	6.5 (.256)	(.472)	21.0 (.827)	(.236)	(.142)	(.252)	(.039)			
	6	FVGS6-6C		6.5 (.256)	11.0 (.433)	7.5 (.295)		22.0 (.866)							
	8	FVGS8-6C		8.4 (.331)	14.0 (.551)	10.0 (.394)		25.0 (.984)							

Note:1) Contact J.S.T. Europe N.V., Belgium for the above tools.

2) Delivery lead times may vary depending on the product. Contact JST for details.

Nylon-insulated

Applicable Wire mm ² (AWG#)	Stud Size Metric	Part No.	Nominal Size	Dimensions mm (in.)									Color	Tool No.	Qty/box
				ød ₂	ød ₃	r	l ₁	l ₂	a	ø d ₁	ø d ₄	s			
0.1 to 0.5(26 to 22)	3	FNGS3-0.5C		3.2 (.126)	5.0 (.197)	5.0 (.197)	8.0(.315)	14.0 (.551)	4.0(.157)	1.0(.039)	2.2(.087)	0.5(.020)	Yellow	JCH-9	2,000
0.25 to 1.5 (22 to 16)	3	FNGS3-1C		3.2 (.126)	6.0 (.236)	4.5 (.177)		16.0 (.630)					Red	JCH-1112	1,000
	3.5	FNGS3.5-1C		3.7 (.146)	6.0 (.236)	4.5 (.177)		16.0 (.630)							
	4	FNGS4-1C		4.3 (.169)	8.0 (.315)	6.0 (.236)	10.0	17.0 (.669)	5.0	1.6	3.4	0.8			
	4	FNGS4M-1C		4.3 (.169)	6.8 (.268)	5.5 (.217)	(.394)	16.0 (.630)	(.197)	(.063)	(.134)	(.031)			
	5	FNGS5-1C		5.3 (.209)	10.0 (.394)	6.5 (.256)		18.0 (.709)							
	6	FNGS6-1C		6.5 (.256)	12.0 (.472)	10.0 (.394)		22.0 (.866)							
>1 to 2.6 (16 to 14)	8	FNGS8-1C		8.4 (.331)	12.0 (.472)	10.0 (.394)		22.0 (.866)					Blue	JCH-1112 JCH-1213	1,000
	3	FNGS3-2.5C		3.2 (.126)	6.0 (.236)	4.5 (.177)		17.0 (.669)							
	3.5	FNGS3.5L-2.5C		3.7 (.146)	6.8 (.268)	4.5 (.177)		17.0 (.669)							
	4	FNGS4S-2.5C		4.3 (.169)	6.8 (.268)	4.5 (.177)	11.0	17.0 (.669)	5.0	2.3	4.4	0.8			
	4	FNGS4-2.5C		4.3 (.169)	8.0 (.315)	6.0 (.236)	(.433)	18.0 (.709)	(.197)	(.091)	(.173)	(.031)			
	5	FNGS5-2.5C		5.3 (.209)	10.0 (.394)	6.5 (.256)		20.0 (.787)							
>2.5 to 6 (12 to 10)	6	FNGS6-2.5C		6.5 (.256)	11.0 (.433)	7.5 (.295)		22.0 (.866)					Yellow	JCH-1213	500
	4	FNGS4-6C		4.3 (.169)	8.0 (.315)	6.0 (.236)	12.0	20.0 (.787)	6.0	3.6	6.4	1.0			
	5	FNGS5-6C		5.3 (.209)	10.0 (.394)	6.5 (.256)	(.472)	21.0 (.827)	(.236)	(.142)	(.252)	(.039)			
	6	FNGS6-6C		6.5 (.256)	11.0 (.433)	7.5 (.295)		22.0 (.866)							
	8	FNGS8-6C		8.4 (.331)	14.0 (.551)	10.0 (.394)		25.0 (.984)							

Note:1) Contact J.S.T. Europe N.V., Belgium for the above tools.

2) Delivery lead times may vary depending on the product. Contact JST for details.