



Search Results

- Evaluate
- FAQ's
- Design a Solution
- Part Drawings
 - PDFMTP Fiber Op ..
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips Within Results

Text Search: 'FX12D5-5M40Y'

Your search criteria matched only one product, shown below

FX12D5-5M40Y



- Pass all TIA/EIA-568-B.3 performance requirements
- FOCIS-5 compliant
- Insertion loss per mated pair: 0.50dB typical; 0.75dB max.
- Tested per IEEE 802.3ae 10 GbE to support network transmission speeds up to 10 Gb/s for link lengths up to 300 meters at 850nm with 50/125 μ m (OM3) laser optimized fiber
- Backward compatible with all 50/125 μ m (OM2) MPO or MTP* system requirements
- Factory terminated and 100% tested for insertion loss
- Insertion loss and return loss data recorded for every *10Gig*TM Multimode Interconnect Cable Assembly
- Lifetime traceability of test data to a Q.C. number on each cable assembly

* MTP is a registered trademark of US Conec Ltd.

Part Number	FX12D5-5M40Y
RoHS Compliancy Status	Compliant
Part Description	Female MTP* to female MTP* 12 fiber interconnect cable assembly (one female MTP* connector on each end on ribbon interconnect cable) – 10 GbE 50/125 μ m.
Product Type	MTP* 12 Fiber Interconnect Cable Assemblies
Length (m)	40
Fiber Compatibility	10 GbE 50/125 μ m
Fiber Type	Multimode
Connector 1 Type	MTP* Connector
Connector 2 Type	MTP* Connector
End Configurations	MTP* to MTP*
Fiber Count	12
Flammability Rating	Plenum (OFNP)
Pricing Description	MTP*MTP* Interconnect Cable Assembly 40m 10 GbE 50m
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.