

# G3VM-61BR1/ER1


MOS FET Relays

Higher power, 3-A switching with a 60-V

load voltage, DIP package.

Low 40 mΩ ON Resistance.

- Continuous load current of 3 A. (Connection C: 6 A)
- Switches minute analog signals.
- Dielectric strength of 2,500 Vrms between I/O.



**NEW**



**Note:** The actual product is marked differently from the image shown here.

**RoHS compliant**

## ■ Application Examples

- Communication equipment
- Test & Measurement equipment
- Security equipment
- Factory Automation equipment
- Power circuit

## ■ Terminal Arrangement/Internal Connections



**Note:** The actual product is marked differently from the image shown here.

## ■ List of Models

Package type	Contact form	Terminals	Load voltage (peak value) *	Model	Minimum package quantity	
					Number per stick	Number per tape and reel
DIP6	1a (SPST-NO)	PCB terminals	60 V	G3VM-61BR1	50	---
		Surface-mounting terminals		G3VM-61ER1		
				G3VM-61ER1 (TR)	---	1,500


\* The AC peak and DC value are given for the load voltage.

## ■ Absolute Maximum Ratings (Ta = 25°C)

Item		Symbol	Rating	Unit	Measurement conditions
Input	LED forward current	I <sub>F</sub>	30	mA	
	Repetitive peak LED forward current	I <sub>FP</sub>	1	A	100 µs pulses, 100 pps
	LED forward current reduction rate	ΔI <sub>F</sub> /°C	-0.3	mA/°C	Ta ≥ 25°C
	LED reverse voltage	V <sub>R</sub>	5	V	
Output	Connection temperature	T <sub>J</sub>	125	°C	
	Load voltage (AC peak/DC)	V <sub>OFF</sub>	60	V	
	Continuous load current	I <sub>O</sub>	3	A	Connection A: AC peak/DC Connection B and C: DC
			3		
			6		
	ON current reduction rate	ΔI <sub>O</sub> /°C	-30	mA/°C	Ta ≥ 25°C
			-30		
			-60		
	Pulse ON current	I <sub>OP</sub>	9	A	t = 100 ms, Duty = 1/10
	Connection temperature	T <sub>J</sub>	125	°C	
	Dielectric strength between I/O (See note 1.)	V <sub>I-O</sub>	2500	Vrms	AC for 1 min
Operating temperature		T <sub>a</sub>	-40 to +85	°C	With no icing or condensation
Storage temperature		T <sub>STG</sub>	-55 to +125	°C	With no icing or condensation
Soldering temperature		---	260	°C	10 s

**Note:** 1. The dielectric strength between the input and output was checked by applying voltage between all pins as a group on the LED side and all pins as a group on the light-receiving side.


### Connection Diagram



## ■ Electrical Characteristics (Ta = 25°C)

Item		Symbol	Minimum	Typical	Maximum	Unit	Measurement conditions
Input	LED forward voltage	V <sub>F</sub>	1.18	1.33	1.48	V	I <sub>F</sub> = 10 mA
	Reverse current	I <sub>R</sub>	---	---	10	µA	V <sub>R</sub> = 5 V
	Capacity between terminals	C <sub>T</sub>	---	70	---	pF	V = 0, f = 1 MHz
	Trigger LED forward current	I <sub>FT</sub>	---	0.5	3	mA	I <sub>O</sub> = 1 A
Output	Maximum resistance with output ON	R <sub>ON</sub>	---	40	70	mΩ	I <sub>F</sub> = 5 mA, I <sub>O</sub> = 2 A, t < 1s
			---	20	---	mΩ	I <sub>F</sub> = 5 mA, I <sub>O</sub> = 2 A, t < 1s
			---	10	---	mΩ	I <sub>F</sub> = 5 mA, I <sub>O</sub> = 4 A, t < 1s
	Current leakage when the relay is open	I <sub>LEAK</sub>	---	---	1.0	µA	V <sub>OFF</sub> = 60 V
Capacity between terminals		C <sub>OFF</sub>	---	1000	---	pF	V = 0, f = 1 MHz
Capacity between I/O terminals		C <sub>I-O</sub>	---	0.8	---	pF	f = 1 MHz, V <sub>s</sub> = 0 V
Insulation resistance between I/O terminals		R <sub>I-O</sub>	1000	---	---	MΩ	V <sub>I-O</sub> = 500 VDC, RoH ≤ 60%
Turn-ON time		t <sub>ON</sub>	---	2	5	ms	I <sub>F</sub> = 5 mA, R <sub>L</sub> = 200 Ω, V <sub>DD</sub> = 20 V (See note 2.)
Turn-OFF time		t <sub>OFF</sub>	---	0.1	1	ms	

**Note:** 2. Turn-ON and Turn-OFF Times




### ■ Recommended Operating Conditions

Use the G3VM under the following conditions so that the Relay will operate properly.


Item	Symbol	Minimum	Typical	Maximum	Unit
Load voltage (AC peak/DC)	$V_{DD}$	---	---	48	V
Operating LED forward current	$I_F$	5	10	25	mA
Continuous load current (AC peak/DC)	$I_O$	---	---	3	A
Operating temperature	$T_a$	-20	---	65	°C

### ■ Engineering Data


#### LED forward current vs. Ambient temperature




#### Continuous load current vs. Ambient temperature




#### LED forward current vs. LED forward voltage




#### Continuous load current vs. On-state voltage




#### On-state resistance vs. Ambient temperature




#### Trigger LED forward current vs. Ambient temperature




#### Turn ON, Turn OFF time vs. LED forward current



#### Turn ON, Turn OFF time vs. Ambient temperature



#### Current leakage vs. Ambient temperature



### ■ Safety Precautions

- Refer to "Common Precautions" for all G3VM models.


# Appearance/Dimensions

DIP6

## ■ Appearance

### DIP (Dual Inline Package)

DIP6



**Note:** The actual product is marked differently from the image shown here.



## ■ Dimensions

(Unit: mm)




PCB Terminals

Weight: 0.4 g




Surface-mounting Terminals

Weight: 0.4 g




PCB Dimensions (Bottom View)



Actual Mounting Pad Dimensions

(Recommended Value, Top View)



**Note:** The actual product is marked differently from the image shown here.

- Application examples provided in this document are for reference only. In actual applications, confirm equipment functions and safety before using the product.
- Consult your OMRON representative before using the product under conditions which are not described in the manual or applying the product to nuclear control systems, railroad systems, aviation systems, vehicles, combustion systems, medical equipment, amusement machines, safety equipment, and other systems or equipment that may have a serious influence on lives and property if used improperly. Make sure that the ratings and performance characteristics of the product provide a margin of safety for the system or equipment, and be sure to provide the system or equipment with double safety mechanisms.

**Note: Do not use this document to operate the Unit.**

**OMRON Corporation**

ELECTRONIC AND MECHANICAL COMPONENTS COMPANY

Contact: [www.omron.com/ecb](http://www.omron.com/ecb)

Cat. No. **K140-E1-02**  
0412(0412)(O)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Omron](#):

[G3VM-61BR1](#) [G3VM-61ER1](#) [G3VM-61ER1\(TR\)](#) [G3VM-61BR1#S](#)