



Home > Products > MICRO SWITCH™ Global Limit Sw itches > GLS DIN > Product Page

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

GLGA12E7B



Actual product appearance may vary.

**Global Limit Switches Series GLS:
Wobble - Coil Spring, 1NC 1NO SPDT
Snap Action, 0.5 in - 14NPT conduit**

Features

Designed to IEC standard for world-wide applications
UL, CSA, and CE
International conduit sizes
Direct PLC interface compatible (two circuit)
Modular construction reduces maintenance parts costs
Designed for ease of installation
Variety of basic switch versions
Wide choice of actuators

Potential Applications

Machine tools: metal fabrication equipment, presses, transfer lines and special machinery
Material handling equipment: conveyors, elevators, cranes, and hoists
Packaging machinery and process equipment
Textile machinery
Construction machinery and equipment, vehicles and lift trucks

Description

The GLS series limit switches are specifically designed for world-wide applications and are supported by Honeywell global resources for sale and after sale service.

Supporting Documentation

- [Installation Instructions](#)
- [Instructions for reading bar charts](#)
- [Engineering Drawing](#)

Product Specifications	
Availability	Global
Operating Force (O.F.)	0,1 N [0.90 in lb]
Pretravel (P.T.)	18°
Differential Travel (D.T.)	8°
Product Type	EN50041/47 Global Limit Switch
Actuator	Wobble - Coil Spring
Lever Style	None
Circuitry	1NC 1NO SPDT Snap Action
Ampere Rating	1 mA to 100 mA
Supply Voltage	12 Vac/Vdc to 250 Vac/Vdc
Housing Material	Zinc Die-Cast
Termination Type	0.5 in - 14NPT conduit
Housing Type	EN50041+ 1 LED+ Plug-in
Series Name	GLS DIN
Shock	50 g per IEC 68-2-27c (w/o Actuator)
Vibration	10 g per IEC 68-2-6 (w/o Actuator)
Sealing	NEMA 1, 4, 12, 13 IP67
Approvals	UL, CSA, CE
CSA File #	LR94369-3
UL File #	E37138 & E157416
Mechanical Life	15 million
Operating Temperature Range	-25 °C to 85 °C [-13 °F to 185 °F]
Agency Approvals and Standards	IEC 947-5-1, EN60947-5-1, UL508
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Sealed	Industrial
Operating Position (O.P.)	26°

My Links

[Login to iCOM](#)
[Login as Rep/AD](#)
[Login as Guest](#)
[Login to Digital University](#)

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (*) to expand search

Specification Search