

NOTES:

- 1. CAST FROM HIGH STRENGTH ELECTRICAL BRONZE
- 2. FURNISHED WITH 3/4" WIDTH X .050" THICK X 6-7/8" LENGTH PURE COPPER CONTACT STRIP
- 3. STEEL PLATED HARDWARE
- 4. INCLUDES CLAMPS & CONDUIT HUBS
- 5. PACKAGE QUANTITY: Q = 25 X = 10

PANDUIT PART NUMBER	CONDUIT HUB SIZE IN.	WATER PIPE RANGE IN.	CONDUCTOR RANGE OF TAP	WIRE DIAMETER RANGE	А	В	С	D	E	F
KLS-0-Q	1/2	1/2-1	10 SOL - 6 STR	.102419	2.31	0.66	1.56	2.37	8.22	2.00
KLS-1-Q	3/4	1/2-1	10 SOL - 2/0 STR	.102419	2.31	0.66	1.56	2.40	8.22	2.00
KLS-1A-X	1	1/2-1	10 SOL - 3/0 STR	.102419	2.31	0.66	1.56	2.90	8.38	2.00



								BRONZE GROUND CLAMPS - KLS SERIES CUSTOMER DRAWING
03	11/10			REVISED WIRE RANGE: ALL PARTS WERE 8 SOL-4 STR REVISED WIRE RANGE FOR ALL PARTS: WAS 10 SOL-2/0 STR	N41361BB-C41361 N41361BB-C41361	FLD FLD	FLD FLD	UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCES ARE: (.X) ± (.XXX) ± UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE GIVEN IN
01	12/04	JHNU		KLS-1A-X WIRE DESCRIPTION FOR 2/0 WAS SOL				DRAWN BY MAT'L: CJW MAT'L: SCALE NONE
00	11/02	CJW	JAC	Drawing released	10520	JAC	LSM	044/04
REV	DATE	BY	СНК	DESCRIPTION	ECN	-R	SUP	P CHK'D JAC C41631 BIZE