


- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: 0.0=±0.4
0.00=±0.25
 3. TERM. NOS. FOR REF. ONLY
 4. ACTUATION FORCE: 130±40gf
 5. TRAVEL TO MAKE: 0.3mm +0.4/-0.0
 6. RATING: 30mA, @12V DC
 7. CONTACT RESISTANCE: 50 milli-ohms typical
 8. DIELECTRIC STRENGTH: 300V RMS min at sea level.
 9. ELECTRICAL LIFE CYCLE: 1,000,000 make & break cycles at full load.
 10. DESIGNATE MAJOR DIMENSIONS
 11. 2002/95/EC (ROHS) COMPLIANT



CIRCUIT: SPST
CONTACT CONFIGURATION

REV.	ECN No.	DESCRIPTION	DATE	CHKD
D	18193	BUTTON LENGTH TOLERANCE CHG.	7/31/08	BLR
C	15472	REMOVED WASHABLE FROM DESC.	10/28/05	C
B	10088	REVISED & REDRAWN	1/27/99	

		TITLE GS 10.00 F130 QP	
SCALE	DATE	DR	DWG
5:1	7/31/08	BLR	L600001
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED		REV	D

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[E-Switch:](#)

[GS10.00F130QP](#)