

## GV2G445

TeSys GV2, TeSys D & K & U - Comb busbar -  
63 A - 4 tap-offs - 45 mm pitch

### Main

|                                                          |                                                    |
|----------------------------------------------------------|----------------------------------------------------|
| Range                                                    | Linergy                                            |
| Product name                                             | FT                                                 |
| Device short name                                        | GV2G                                               |
| Product or component type                                | Comb busbar                                        |
| Accessory / separate part category                       | Connection accessory                               |
| Poles description                                        | 3P                                                 |
| Range compatibility                                      | TeSys - U<br>TeSys - K<br>TeSys - GV2<br>TeSys - D |
| Number of tap-offs                                       | 4                                                  |
| [I <sub>th</sub> ] conventional free air thermal current | 63 A                                               |
| Connection pitch                                         | 45 mm                                              |

### Complementary

|                                            |             |
|--------------------------------------------|-------------|
| Mounting location                          | On terminal |
| [U <sub>i</sub> ] rated insulation voltage | 690 V       |
| Product weight                             | 0.077 kg    |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[GV2G445](#)