


Description

- In-Line Fuseholders for MINI® Fuses.
- Voltage Rating: 32Vdc maximum
- Current Rating: See Table
- Body material withstands high temps. Protective cover has removable straps.

Ordering

- Specify packaging and product code



MINI® Fuse Blade Type Holder

Catalog No.	Description	Fuse Size	Electrical Connection	Maximum Continuous Current Rating
HHL	Black fuseholder w/cover	2-20A	#16 black lead wire; 4" length stripped to 1/4"	16A*
HHL-B	Black fuseholder - Body only			
HHM	Black fuseholder w/cover	2-30A	#12 red lead wire; 4" length stripped to 1/4"	24A*
HHM-B	Black fuseholder - Body only			
HHM-C	Black cover only			

Bulk Products (Bulk Quantity - 1000 Pieces)

Catalog No.	Description	Fuse Size	Electrical Connection	Maximum Continuous Current Rating
BK/HHL-R	Black fuseholder - Body only	2-20A	#16 red lead wire; 4" length stripped to 1/4"	16A*

* or 80% of fuse rating, whichever is less

A fuse must be properly and fully inserted into the holder to provide a solid connection. Poor or improper insertion of the fuse can result in failure of the fuse and holder, thus not protecting the device for which it was intended.

PACKAGING CODE	
Packaging Code	Description
BK	1,000 pieces in a box

North America

Cooper Electronic Technologies
1225 Broken Sound Parkway NW
Suite F
Boca Raton, FL 33487-3533
Tel: 1-561-998-4100
Fax: 1-561-241-6640
Toll Free: 1-888-414-2645

Cooper Bussmann
P.O. Box 14460
St. Louis, MO 63178-4460
Tel: 1-636-394-2877
Fax: 1-800-544-2570

Europe

Cooper Electronic Technologies
Cooper (UK) Limited
Burton-on-the-Wolds
Leicestershire • LE12 5TH UK
Tel: +44 (0) 1509 882 737
Fax: +44 (0) 1509 882 786

Cooper Electronic Technologies
Avda. Santa Eulalia, 290
08223
Terrassa, (Barcelona), Spain
Tel: +34 937 362 812
+34 937 362 813
Fax: +34 937 362 719

Asia Pacific

Cooper Electronic Technologies
1 Jalan Kilang Timor
#06-01 Pacific Tech Centre
Singapore 159303
Tel: +65 278 6151
Fax: +65 270 4160

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Eaton:](#)
[HHM-CU](#)