




THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

NOTES:

1. UL LISTED
2. MATERIAL: EXTRUDED COPPER
3. FOR COPPER WIRE ONLY



LISTED
508D



CATALOG NUMBER	CONDUCTOR RANGE	NAVY CABLE SIZE	APPROXIMATE DIMENSIONS							WRENCH SIZE	TORQUE VALUE IN-LBS
			A	C	S	H	L	X	T		
HL1-25-X	14 SOLID - 3 STR.	4-14	0.56	0.81	0.28	0.79	1.38	0.31	0.19	SCREW DRIVER SLOT	20
HL4-1-X	8 SOLID - 4 STR.	23-40	0.56	0.81	0.28	0.79	1.38	0.31	0.19	SCREW DRIVER SLOT	35

REV	DATE	BY	CHK	DESCRIPTION	ECN
00	7/08	JHNU	JHNU	DRAWING RELEASED - MOVED FROM DWG C41181	

PANDUIT CORP. TINLEY PARK, ILLINOIS

ONE BOLT HOLE PREMIUM CONNECTOR TYPE HL
(HL1-25-X, HL4-1-X)
CUSTOMER DRAWING

SCALE N/A DRAWING NO / CAD FILE C41758_00

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Panduit:](#)

[HL4-1-X](#) [HL1-25-X](#)