



NOTE-2: COMPATIBLE WITH NARROW AND WIDE BODY
 NOTE-3: PCB FINISH HOLE DIAMETER SEE GS-12-447
 NOTE-4: INSERTION TOOLING PROCESS
 - See drawings: C-8626-1010, C-8626-1011, C-8626-1012, C-8626-1013

GENERAL CHARACTERISTICS AND ROHS INFORMATIONS:
 SEE GS-12-447

TIN LEAD PART NUMBER

Part Number:	HM1S4x FGR000H6	
PIN COUNT	024 WAYS-REPLACE x BY 1	096 WAYS-REPLACE x BY 3
RANGE	048 WAYS-REPLACE x BY 2	192 WAYS-REPLACE x BY 4

LEAD-FREE PART NUMBER

Part Number:	HM1S4x FGR000H6LF	
PIN COUNT	024 WAYS-REPLACE x BY 1	096 WAYS-REPLACE x BY 3
RANGE	048 WAYS-REPLACE x BY 2	192 WAYS-REPLACE x BY 4

rev	ecn no	dr	date
A	-	CHA	1999/09/22
B	LS05-004	MLE	2005/02/21
C	LS06-0095	LGO	2006/07/14
D	LS07-0266	MLE	2007/11/08
-	-	-	-
-	-	-	-
-	-	-	-

www.fciconnect.com		surface ISO 1302 ✓	tolerance std ISO 406 ISO 1101	projection 	mm
TOLERANCES UNLESS OTHERWISE SPECIFIED					
Dr	CHAILLEUX	1999/09/22	ANGULAR	0.X	±0.1
Eng	LENOIR	1999/09/22	LINEAR	0.XX	±0.1
Chr	LEGARE	1999/09/22	0.XX' ±2'	0.XXX	±0.1
Appr	LEGARE	1999/09/22	Product family		METRAL
title HM1 FEMALE STRAIGHT PRESS FIT				size A3	
catalog no				Scale 3.5	
4 ROWS - PCB THICKNESS: 1.6 mm				ECN LS07-0266	
CUSTOMER				Spec ref -	
C-8626-0998				Rev. D	
sheet 1 of 1					