



[> PN Search](#)

Millipacs™
HM2P88PNA124GF

[> Communications Data
& Consumer division](#)
FCI brings you more
[✉ Contact our sales/
technical support](#)
[✉ Sample request](#)
[€ Price request](#)
[📊 Check distributor stock](#)
[Home page](#)
[Product quick search](#)

P/N Search

FCI Competitor

GO

RoHS/LF P/N
Search

Product type search

Alphabetical list

Connection type

Markets / Applications

[Product finder](#)
[Literature](#)
[Services](#)
[Contact us](#)
[Registered users](#)
[Forgot password ?](#)
[Register now](#)

Download	Mating half	Alternative parts	Application tooling
> Customer Drawing > Product Specification > 3D Model	Not Available	Not Available	www.foehrenbach.be Americas Asia Pacific

Features Selected

Product Type	Header
Contact Finish	Level 2 (0.8 microns / 30u" Gold) RPU
Series	Module type E
Gender	Header
Orientation	Straight
#ofRows	8
# of Positions	200
Tail Lengths	Rear Mating Tails Level 3 (16.0mm)
PCB Mounting	Press-fit
Shielded?	yes

Other Properties

Housing Material	High Temperature Thermoplastic (UL94 V-0)
Contact Base Material	Phosphor Bronze
Operating Temperature	-55°C to +125°C
Signal Contact Current Rating	1.5 A @ 20°C, 1.0 A @ 70°C
Signal Contact Test Voltage (Fully Loaded)	750 Vrms
Signal Contact, Contact Resistance	20 milli ohms max
Signal Contact Insulation Resistance	10000 mega ohms min
Signal Contact Mating Force	0.75 N max per contact pair
Signal Contact Withdrawal Force	0.15 N min per contact pair
Signal Contact Hertz Stress	200 Kpsi min
Contact Levels	Refer to Customer Drawing
Signal Contact Normal Force	0.75 N min (EOL)
Approvals and Certification	UL and CSA Certified