

Search Results

Evaluate

- FAQ's

How to Buy

- Bill of Material

- Favorite Products List

- Locate Distributor

[Home](#) > [Products Overview](#) > [Search Results](#) >

Current refinements (click  to remove) [Search Tips](#)

 **Text Search: 'HSTT06-M5'**

Your search criteria matched only one product, shown below

HSTT06-M5



Flexible Polyolefin DRY-SHRINK™ Heat Shrink Tubing

- General Purpose heat shrink tubing for dry locations
- Applications include insulating, protecting, harnessing and identifying wires.
- Material Type: Crosslinked Polyolefin
- Shrink Ratio: 2:1
- Temperature Range: -67°F to 275°F (-55°C to 135°C)
- Flammability Rating: Flame retardant EXCEPT clear
- Voltage: 600 V
- UL Recognized, CSA Certified
- Mil Spec: AMSDTL-23053/5 Class 1 (Colors) Class 2 (Clear)

| | |
|--|---|
| Part Number | HSTT06M5 |
| RoHS Compliance Status | Compliant |
| Part Description | Thin Wall Polyolefin Heat Shrink |
| Material | Polyolefin cross-linked |
| Color | Green |
| CSA Certified | Yes |
| Military Specification | AMS-DTL-23053/5 Class 1 |
| UL Recognized | E122770 |
| CE Compliant | No |
| CE Marking | No |
| Flammability Rating | Flame Retardant |
| Length Per Reel (ft.) | 1000 |
| Length Per Reel (m) | 304.8 |
| Max. Recovered I.D. (In.) | .031 |
| Max. Recovered I.D. (mm) | .8 |
| Min. Expanded I.D. (In.) | .063 |
| Min. Expanded I.D. (mm) | 1.6 |
| Nominal Diameter / Size | .063 |
| Nominal Recovered Wall Thickness (In.) | .017 |
| Nominal Recovered Wall Thickness (mm) | .4 |
| Pricing Description | Heat Shrink Thin, .06"(1.6mm) Dia, Green |
| Shrink Ratio | 2:1 |
| Temperature Range | -67°F to 275°F (55°C to 135°C) |
| Min. Order UOM | RL |
| Min. Order Qty. | 1 |
| BOM Qty. (# of Pkgs.) | <input type="text" value="0"/> |
| Add to Favorite Product List |  |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.