



Network and Electrical Solutions

UNIFIED PHYSICAL INFRASTRUCTURESM

Worldwide |

[Home](#)[Industries](#)[Solutions](#)[Products](#)[Partners](#)[Support](#)[About Us](#)[Careers](#)[Entire Site](#)

Search Results

Evaluate

[- FAQ's](#)

How to Buy

[- Bill of Material](#)[- Favorite Products List](#)[- Locate Distributor](#)

[Home](#) > [Products Overview](#) > [Search Results](#) >

Current refinements (click to remove) [Search Tips](#) Within Results

Text Search: 'HSTT09-48-TLC'

Your search criteria matched only one product, shown below

HSTT09-48-TLC



- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
- Cross-linked, UV resistant material improves flame retardancy, chemical, and temperature resistance

For clear, add "C" to end of part number package suffix (Example HSTT05-48-QC). Contact customer service for additional color information.

^ Meets Mil Spec AMS-DTL-23053/5 Class 1(Colors), Class 2 (Clear)

- Part Number
- RoHS Compliance Status
- Part Description
- Material
- Color
- Military Specification
- Length (ft.)

HSTT09-48-TLC
Compliant
Thin Wall Polyolefin Heat Shrink
Flame retardant polyolefin cross-linked except clear^
Clear
AMS-DTL-23053/5 Class 2

4

▪ Length (m)	1.2
▪ Max. Recovered I.D. (In.)	.046
▪ Max. Recovered I.D. (mm)	1.2
▪ Min. Expanded I.D. (In.)	.093
▪ Min. Expanded I.D. (mm)	2.4
▪ Nominal Diameter / Size	.093
▪ Nominal Recovered Wall Thickness (In.)	.020
▪ Nominal Recovered Wall Thickness (mm)	.5
▪ Pricing Description	Heat Shrink Thin, .09"(2.4mm) Dia, Clear
▪ Shrink Ratio	2:1
▪ Temperature Range	-67°F to 275°F (-55°C to 135°C)
▪ Min. Order UOM	PC
▪ Min. Order Qty.	250
▪ BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
▪ Add to Favorite Product List	<input type="checkbox"/>

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

[Home](#) | [Industries](#) | [Solutions](#) | [Products](#) | [Partners](#) | [Support](#) | [Contact Us](#) | [Site Map](#) | [Careers](#)

Copyright © 1995-2008, PANDUIT CORP. All rights reserved. | [Legal Information](#) | [Privacy Policy](#)