



Search Results

Evaluate

- FAQ's

How to Buy

- Bill of Material

- Favorite Products List

- Locate Distributor

[Home](#) > [Products Overview](#) > [Search Results](#) >

Current refinements (click to remove)    [Search Tips](#)

**Text Search: 'HSTT75-Q45'**

Your search criteria matched only one product, shown below

## HSTT75-Q45



Flexible Polyolefin DRY-SHRINK<sup>TM</sup> Heat Shrink Tubing in 25 ft. Reels

- General purpose heat shrink tubing for dry locations
- Applications include insulating, protecting, harnessing and identifying wires
- Material Type: Crosslinked Polyolefin
- Shrink Ratio: 2:1
- Temperature Range: -67°F to 275°F (-55°C to 135°C)
- Flammability Rating: Flame Retardant EXCEPT Clear
- Voltage: 600V
- UL Recognized, CSA Certified
- Mil Spec: AMSDTL-23053/5 Class 1 (Colors) Class 2 (Clear)

|  |                                        |                                                  |
|--|----------------------------------------|--------------------------------------------------|
|  | Part Number                            | HSTT75Q45                                        |
|  | RoHS Compliance Status                 | Compliant                                        |
|  | Part Description                       | Thin Wall Polyolefin Heat Shrink                 |
|  | Material                               | Polyolefin cross-linked                          |
|  | Color                                  | Yellow/Green                                     |
|  | CSA Certified                          | Yes                                              |
|  | Military Specification                 | AMS-DTL-23053/5 Class 1                          |
|  | UL Recognized                          | E122770                                          |
|  | CE Compliant                           | No                                               |
|  | CE Marking                             | No                                               |
|  | Flammability Rating                    | Flame Retardant                                  |
|  | Length Per Reel (ft.)                  | 25                                               |
|  | Length Per Reel (m)                    | 7.6                                              |
|  | Max. Recovered I.D. (In.)              | .375                                             |
|  | Max. Recovered I.D. (mm)               | 9.5                                              |
|  | Min. Expanded I.D. (In.)               | .750                                             |
|  | Min. Expanded I.D. (mm)                | 19.0                                             |
|  | Nominal Diameter / Size                | .750                                             |
|  | Nominal Recovered Wall Thickness (In.) | .030                                             |
|  | Nominal Recovered Wall Thickness (mm)  | .8                                               |
|  | Pricing Description                    | Heat Shrink Thin, .75"(19.0mm) Dia, Yellow/Green |
|  | Shrink Ratio                           | 2:1                                              |
|  | Temperature Range                      | -67°F to 275°F (55°C to 135°C)                   |
|  | Min. Order UOM                         | RL                                               |
|  | Min. Order Qty.                        | 1                                                |
|  | BOM Qty. (# of Pkgs.)                  | <input type="text" value="0"/>                   |
|  | Add to Favorite Product List           |                                                  |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.