

Inductors

Commercial, Molded, Shielded



FEATURES

- Wide inductance range in small package
- Flame retardant coating
- Electromagnetic shield-finest shield available
- Epoxy molded construction provides superior moisture protection
- Precision performance, excellent reliability, sturdy construction



RoHS
COMPLIANT

ELECTRICAL SPECIFICATIONS

Inductance Tolerance: $\pm 10\%$ standard, $\pm 5\%$ available

Insulation Resistance: 1000 Megohm minimum per MIL-STD-202, Method 302, Test Condition B

Dielectric Withstanding Voltage: 1000 VAC per MIL-STD-202, Method 301 (sea level)

Percent Coupling: 3 % maximum per MIL-PRF-15305

Operating Temperature: - 55 °C to + 105 °C

MECHANICAL SPECIFICATIONS

Terminals: 5 pounds pull per MIL-STD-202, Method 211, Test Condition A

Weight: IMS-5 = 0.85 grams maximum

MATERIAL SPECIFICATIONS

Encapsulant: Epoxy

Standard Terminals: #22 AWG tinned copper

INDUCTANCE RANGE AND MILITARY STANDARD			
INDUCTANCE RANGE		MATERIAL	
FROM	TO	CORE	SHIELD
0.10 μ H	0.82 μ H	Phenolic	Powd. Iron
1.0 μ H	12.0 μ H	Powd. Iron	Powd. Iron
15.0 μ H	100000 μ H	Ferrite	Ferrite

ENVIRONMENTAL PERFORMANCE		
TEST	CONDITIONS	SPECIFICATIONS
Barometric Pressure	Test Condition C	MIL-STD-202, Method 105
Thermal Shock	Test Condition A-1	MIL-STD-202, Method 107
Flammability	-	MIL-STD-202, Method 111
Overload	-	MIL-PRF-15305
Low Temperature Storage	-	MIL-PRF-15305
Resistance to Soldering Heat	Test Condition A	MIL-STD-202, Method 210
Resistance to Solvents	-	MIL-STD-202, Method 215



STANDARD ELECTRICAL SPECIFICATIONS							
IND. (μ H)	TOL.	Q MIN.	TEST FREQ. L & Q (MHz)	SELF-RESONANT* FREQ MIN. (MHz)	DCR AT 25 °C MAX. (Ohms)	RATED DC** CURRENT (mA)	INCREMENTAL** CURRENT (mA)
0.10	$\pm 10\%$	50	25.0	250.0	0.025	1790	-
0.12	$\pm 10\%$	51	25.0	250.0	0.034	1530	-
0.15	$\pm 10\%$	51	25.0	250.0	0.037	1470	-
0.18	$\pm 10\%$	50	25.0	250.0	0.047	1300	-
0.22	$\pm 10\%$	49	25.0	250.0	0.067	1100	-
0.27	$\pm 10\%$	47	25.0	250.0	0.11	855	-
0.33	$\pm 10\%$	46	25.0	250.0	0.13	780	-
0.39	$\pm 10\%$	44	25.0	250.0	0.18	670	-
0.47	$\pm 10\%$	44	25.0	235.0	0.25	565	-
0.56	$\pm 10\%$	43	25.0	210.0	0.33	490	-
0.68	$\pm 10\%$	42	25.0	190.0	0.45	420	-
0.82	$\pm 10\%$	40	25.0	180.0	0.59	370	-
1.0	$\pm 10\%$	44	25.0	140.0	0.07	1070	-
1.2	$\pm 10\%$	44	7.9	130.0	0.10	895	-
1.5	$\pm 10\%$	44	7.9	115.0	0.12	815	-
1.8	$\pm 10\%$	44	7.9	105.0	0.14	775	-
2.2	$\pm 10\%$	44	7.9	100.0	0.19	650	-
2.7	$\pm 10\%$	44	7.9	92.0	0.28	535	-
3.3	$\pm 10\%$	44	7.9	85.0	0.35	480	-

* Measured with full length lead.

** **Rated DC Current:** Based on maximum temperature rise not to exceed 15 °C at + 90 °C ambient.

*** **Incremental Current:** The minimum typical current at which the inductance will be decreased by 5 % from its initial zero DC value.

**STANDARD ELECTRICAL SPECIFICATIONS**

IND. (μ H)	TOL.	Q MIN.	TEST FREQ. L & Q (MHz)	SELF-RESONANT* FREQ MIN. (MHz)	DCR AT 25 °C MAX. (Ohms)	RATED DC** CURRENT (mA)	INCREMENTAL** CURRENT (mA)
3.9	$\pm 10\%$	44	7.9	75.0	0.40	450	-
4.7	$\pm 10\%$	44	7.9	70.0	0.55	380	-
5.6	$\pm 10\%$	44	7.9	65.0	0.72	335	-
6.8	$\pm 10\%$	50	7.9	55.0	1.02	280	-
8.2	$\pm 10\%$	50	7.9	50.0	1.32	250	-
10.0	$\pm 10\%$	50	7.9	46.0	1.62	220	-
12.0	$\pm 10\%$	55	2.5	44.0	2.00	200	-
15.0	$\pm 10\%$	45	2.5	49.0	0.80	315	250.0
18.0	$\pm 10\%$	45	2.5	45.0	0.89	300	235.0
22.0	$\pm 10\%$	45	2.5	41.0	0.96	290	220.0
27.0	$\pm 10\%$	45	2.5	38.0	1.19	260	200.0
33.0	$\pm 10\%$	45	2.5	34.0	1.37	240	190.0
39.0	$\pm 10\%$	50	2.5	29.0	1.93	205	180.0
47.0	$\pm 10\%$	50	2.5	27.0	2.11	195	175.0
56.0	$\pm 10\%$	50	2.5	25.0	2.23	190	160.0
68.0	$\pm 10\%$	50	2.5	21.0	2.70	170	150.0
82.0	$\pm 10\%$	50	2.5	10.5	2.44	180	140.0
100.0	$\pm 10\%$	50	2.5	10.0	3.12	160	120.0
120.0	$\pm 10\%$	55	0.79	9.7	3.6	150	95.0
150.0	$\pm 10\%$	55	0.79	8.5	4.1	140	90.0
180.0	$\pm 10\%$	55	0.79	8.0	4.4	135	85.0
220.0	$\pm 10\%$	55	0.79	7.5	5.0	125	80.0
270.0	$\pm 10\%$	55	0.79	7.0	5.8	115	70.0
330.0	$\pm 10\%$	55	0.79	6.5	6.4	110	65.0
390.0	$\pm 10\%$	60	0.79	6.2	7.4	105	60.0
470.0	$\pm 10\%$	60	0.79	5.7	9.5	92	58.0
560.0	$\pm 10\%$	60	0.79	4.7	10.5	90	55.0
680.0	$\pm 10\%$	60	0.79	4.5	11.8	80	50.0
820.0	$\pm 10\%$	60	0.79	4.2	13.0	80	45.0
1000.0	$\pm 10\%$	60	0.79	3.8	17.5	70	40.0
1200.0	$\pm 10\%$	45	0.25	1.5	22.1	60	35.0
1500.0	$\pm 10\%$	45	0.25	1.2	26.5	55	33.0
1800.0	$\pm 10\%$	45	0.25	1.0	29.9	50	30.0
2200.0	$\pm 10\%$	45	0.25	0.97	33.8	50	27.0
2700.0	$\pm 10\%$	45	0.25	0.92	47.3	40	25.0
3300.0	$\pm 10\%$	45	0.25	0.84	53.0	40	22.0
3900.0	$\pm 10\%$	45	0.25	0.80	73.8	35	20.0
4700.0	$\pm 10\%$	45	0.25	0.74	81.6	31	19.0
5600.0	$\pm 10\%$	44	0.25	0.73	98.9	28	17.0
6800.0	$\pm 10\%$	40	0.25	0.66	111.0	27	16.0
8200.0	$\pm 10\%$	40	0.25	0.54	119.0	26	15.0
10000.0	$\pm 10\%$	40	0.25	0.47	137.0	24	14.0
12000.0	$\pm 10\%$	30	0.079	0.33	143.0	23	13.0
15000.0	$\pm 10\%$	30	0.079	0.29	157.0	22	12.0
18000.0	$\pm 10\%$	30	0.079	0.28	175.0	21	10.0
22000.0	$\pm 10\%$	27	0.079	0.25	274.0	17	9.0
27000.0	$\pm 10\%$	27	0.079	0.21	308.0	16	8.0
33000.0	$\pm 10\%$	27	0.079	0.19	343.0	15	7.5
39000.0	$\pm 10\%$	27	0.079	0.17	376.0	15	6.0
47000.0	$\pm 10\%$	23	0.079	0.16	473.0	13	5.5
56000.0	$\pm 10\%$	23	0.079	0.14	512.0	13	5.0
68000.0	$\pm 10\%$	23	0.079	0.13	580.0	12	4.0
82000.0	$\pm 10\%$	21	0.079	0.12	618.0	11	3.5
100000.0	$\pm 10\%$	18	0.079	0.11	678.0	11	3.0

* Measured with full length lead.

** **Rated DC Current:** Based on maximum temperature rise not to exceed 15 °C at + 90 °C ambient.*** **Incremental Current:** The minimum typical current at which the inductance will be decreased by 5 % from its initial zero DC value.**DESCRIPTION**

IMS-5	10 μ H	$\pm 10\%$	ER	e2
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD

GLOBAL PART NUMBER INFORMATION

I	M	S	0	5	E	R	1	0	0	K
MODEL					PACKING CODE		INDUCTANCE VALUE			TOL.



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.