



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: INTERNET525U

### Internet Office UPS System - All-in-one SOHO Solution

#### Highlights

- 6 outlets (3 UPS/surge, 3 surge-only)
- Built-in RJ11 jacks provide complete modem/fax surge protection
- USB port and free software facilitate unattended shutdown
- Compact cabinet design fits easily on or under any desk
- \$100,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

#### Description

Tripp Lite's INTERNET525U standby UPS offers complete protection for PCs, workstations and other sensitive electronics in an attractive ultra-compact, mountable housing. Prevents data loss and system downtime by providing battery supported AC output during brownouts and blackout conditions. 8 widely spaced output receptacles accommodate large transformer plugs without blocking outlets. 4 outlets with full battery support and surge suppression protect computers, monitors and other vital system components from loss of power. 4 additional outlets with surge suppression-only are ideal for printers and other accessories not requiring battery support. Single line telephone suppression jacks with line splitter protects up to two directly connected modems, fax machines, cordless phones or other peripherals sharing a standard dialup or DSL phone line connection. USB port with PowerAlert monitoring software and cabling enables safe unattended system shutdown in the case of extended power failure. Audible alarm and front panel LEDs offer status information regarding line and battery power operation. 525VA/300 watt power handling ability supports entry-level PCs for up to 17 minutes during power failures. 2 year warranty. \$100,000 [connected equipment insurance](#) (USA & Canada Only).

#### Applications

- Basic PCs for home/home-office use, network workstations, audio/video equipment, home entertainment systems and other sensitive electronic devices.

#### Package Includes

- INTERNET525U UPS System
- Warranty information
- Instruction manual

#### Features

- INTERNET525U standby UPS offers protection from blackouts, brownouts and surges on both AC and dialup modem lines
- Provides seamless battery support so that connected equipment can be shutdown without data loss
- 3 battery supported outlets protect computer, monitor and one vital system peripheral, plus 3 additional surge suppression-only outlets for printers and other system accessories not requiring battery support
- Lightweight, ultra-compact, flat-pack housing offers an appearance closer to a power strip than most traditional bulky UPS designs
- Attractive stealth black UPS color scheme
- USB port enables automatic system shutdown if power fails while the system runs unattended
- USB port supports on battery, low battery and power restored messaging, timed and inverter shutoff after unattended shutdown
- PowerAlert UPS monitoring software available via free download from [www.tripplite.com](http://www.tripplite.com), USB cable included
- Compatible with Tripp Lite's optional Watchdog service software
- Built-in single line RJ11 phone suppression jacks with line splitter protects up to two directly connected peripherals with a standard dialup phone connection, phone cable included

- Built-in audible alarm and front panel LEDs offer continuous status information regarding line and battery power operation
- 525VA/300 watt power handling ability supports entry-level PC systems for up to 15 minutes during power fail conditions
- Includes attached 6 ft. AC power cord, on/off power switch
- Compatible with 120V/60Hz applications in USA, Canada, Mexico and other countries
- 2 year warranty. \$100,000 [connected equipment insurance](#) (USA & Canada Only)

## Specifications

OUTPUT	
Frequency compatibility	60 Hz
Output VA	525
Output watts	300
Output nominal voltage	120VAC
Output voltage regulation	LINE MODE: Passes sine wave line voltage from 100-141V to connected equipment unchanged BATTERY MODE: PWM sine wave output 120V +/-5%
Output frequency regulation	LINE MODE: Passes line frequency of 60Hz +/-10% BATTERY MODE: Inverter output regulated to 60Hz +/-0.5Hz
Outlet quantity / type	6 NEMA 5-15R output receptacles (3 with UPS and surge suppression / 3 with surge suppression only)
INPUT	
UPS Input cord length (ft.)	6 ft., 16 gauge
Recommended Electrical Service	15A 120V
Maximum Input Amps (A)	12
Maximum Input Watts	1440
Input connection type	NEMA 5-15P
Voltage compatibility (VAC)	120
BATTERY	
DC system voltage (VDC)	12
Battery Access	User replaceable batteries are accessible via user accessible battery door
Full load runtime	3 minutes (450VA)
Half load runtime	10 minutes (250VA)
Typical battery lifespan	3-6 years, depending on usage
Battery recharge rate	2-4 hours to 90%
LEDS ALARMS & SWITCHES	
Alarms	Two program audible alarm beeps at regular intervals to indicate battery backup operation. Continuous alarm tone indicates the UPS is running on battery power and is nearly depleted. Alarm also sounds during self-test operation.
Switches	Combination power off / on / self-test push button switch
Front panel LEDs	2 LEDs indicate line power, battery power status

<b>SURGE / NOISE SUPPRESSION</b>	
<b>UPS AC suppression joule rating</b>	1170 joules
<b>EMI / RFI AC noise suppression</b>	Yes
<b>AC suppression response time</b>	Instantaneous
<b>Dataline suppression</b>	Single line TEL/DSL surge suppression with RJ-style phone connectors (center 2 wires protected, 260V clamping), includes phone cable
<b>PHYSICAL</b>	
<b>Shipping weight (lbs)</b>	11.8
<b>Shipping weight (kg)</b>	5.4
<b>Cooling method</b>	Convection
<b>Unit Dimensions (HWD/in)</b>	4 x 12 x 7
<b>Unit Dimensions (HWD/cm)</b>	10.2 x 30.5 x 17.8
<b>Shipping Dimensions (HWD/in)</b>	5.5 x 14.5 x 9.75
<b>Shipping Dimensions (HWD/cm)</b>	14 x 36.8 x 24.8
<b>Unit weight (lbs)</b>	7.75
<b>Unit weight (kg)</b>	3.5
<b>Material of construction</b>	ABS
<b>Form factors supported</b>	Ultra-compact desk/floor mount , mounting flanges enable wall-mount installation
<b>ENVIRONMENTAL</b>	
<b>Relative Humidity</b>	0 to 95%, non-condensing
<b>Line mode BTU/hr. (Max.)</b>	26.2
<b>Battery mode BTU/hr. (Max.)</b>	88.7
<b>COMMUNICATIONS</b>	
<b>WatchDog compatibility</b>	Yes, compatible with Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications
<b>Network monitoring port</b>	Single built-in USB port supports on battery, low battery and power restored messaging. Interface supports timed inverter shutoff after unattended shutdown. Compatible with Tripp Lite's PowerAlert and Watchdog service software
<b>Software and cabling included</b>	Includes USB cable and PowerAlert UPS monitoring software
<b>LINE / BATTERY TRANSFER</b>	
<b>Transfer time from line power to battery mode</b>	2-4 milliseconds

<b>Low voltage transfer to battery power</b>	approx. 100VAC
<b>High voltage transfer to battery power</b>	approx. 141VAC
<b>SPECIAL FEATURES</b>	
<b>Appearance</b>	Attractive black ultra-compact housing
<b>Cold Start</b>	Yes, inverter can be "cold started" to enable temporary AC output during a power failure
<b>CERTIFICATIONS</b>	
<b>Certifications</b>	Tested to UL1778 (USA), cUL (Canada), FCC Class B (emissions), NOM (Mexico), FCC Part 68 / Industry Canada (telecommunications)
<b>WARRANTY</b>	
<b>Product Warranty Period (U.S., Canada &amp; Puerto Rico)</b>	2-year limited warranty
<b>Connected Equipment Insurance (U.S., Canada &amp; Puerto Rico)</b>	\$100,000 Ultimate Lifetime Insurance
<b>Optional Coverage</b>	Optional 3 and 5 year on site or factory warranties available for select opportunities, contact Tripp Lite for more information

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=2003](http://www.tripplite.com/en/products/model.cfm?txtModelID=2003).

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.