

## 6 outlet, 6ft cord, 2850 joules, 2-line coaxial, 1-line tel/modem, All-metal housing Isobar Surge Suppressor

MODEL NUMBER: ISOBAR6DBS



### Description

Tripp Lite's ISOBAR6DBS Isobar Home/Business Theater Surge Suppressor provides premium protection--2850 joules--stopping damaging surges and filtering disruptive line noise so components perform at their peak! You can see and hear the difference: sharper, crisper video; deeper, fuller audio and longer component life spans. Perfect for small-to-medium home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more. Exclusive Isolated Filter Banks eliminate noise interference between components. 6 outlets (with transformer spacing and plug-in safety covers), 2-line 2.2 GHz gold coaxial protection and 1-line tel/modem protection safeguard an entire home/business theater system. \$250,000 Ultimate Lifetime Insurance coverage (USA and Canada only). Includes all-metal housing, three diagnostic LEDs, 6-ft. cord with a right-angle plug, 6-ft. coaxial cable and 6-ft. phone cord.

### Features

- 2850 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- \$250,000 Ultimate Lifetime Insurance (USA and Canada only) covers connected components against surge damage...for life!
- Isolated Filter Banks eliminate interference between connected components
- All-metal housing safely withstands the strongest surges
- 6 surge-protected NEMA 5-15R AC outlets safeguard an entire home/business theater system
- Widely spaced outlets accommodate up to 3 transformers
- Four plug-in safety covers protect against accidental contact
- 2 sets of 2.2GHz gold coaxial protection to safeguard components on cable, satellite or antenna line (includes 6-ft gold coax cable)
- 1-line tel/modem surge protection (with included 6-ft. phone cord) safeguards personal video recorders (PVRs) on a single dial-up line.
- 6-ft. cord with right-angle NEMA 5-15P plug provides convenient location anywhere within a home/business theater system
- 3 diagnostic LEDs alert user to protection, line power and fault status
- Keyhole slots provide convenient wall or cabinet mounting
- Illuminated master switch provides one-touch power control over all components. Circuit breaker protects against dangerous system overload

### Highlights

- 6 outlets / 6-ft. cord
- 2850 joule rating
- Isolated Filter Banks / all-metal housing
- 2-line 2.2 GHz gold coaxial protection
- 1-line tel/modem surge protection
- \$250,000 Ultimate Lifetime Insurance (USA and Canada only)

### Applications

- Perfect for small-to-medium home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more

### Package Includes

- ISOBAR6DBS Home/Business Theater Surge Suppressor
- 6 ft. gold coaxial cable
- 6 ft. phone cord
- Instruction manual with warranty information



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

- All-metal housing (black) stands up to the most demanding environments
- UL and cUL listed

## Specifications

| OVERVIEW                           |                                                                                     |
|------------------------------------|-------------------------------------------------------------------------------------|
| Intended Application               | Home/Office, Computer Networks, Audio/Video                                         |
| OUTPUT                             |                                                                                     |
| Frequency compatibility            | 50 / 60 Hz                                                                          |
| Output watts                       | 1440                                                                                |
| Circuit Breaker (amps)             | 12                                                                                  |
| Outlet quantity / type             | 6 NEMA 5-15R                                                                        |
| Transformer accommodation          | Accommodates 3 transformers                                                         |
| INPUT                              |                                                                                     |
| Nominal Input Voltage(s) Supported | 120V AC                                                                             |
| Recommended Electrical Service     | 120V (110-125V)                                                                     |
| Input connection type              | NEMA 5-15P                                                                          |
| Input plug features                | Space-saving right angle input plug                                                 |
| Input cord length (ft.)            | 6                                                                                   |
| Input cord length (m)              | 1.8                                                                                 |
| Input cord gauge, type             | 14 gauge, SJT                                                                       |
| Voltage compatibility (VAC)        | 120                                                                                 |
| Maximum Surge Amps                 | 135000                                                                              |
| UPC ASSIGNMENT                     |                                                                                     |
| Unit Carton UPC#                   | 037332011213                                                                        |
| LEDS ALARMS & SWITCHES             |                                                                                     |
| Switches                           | Combination AC circuit breaker and two position red illuminated on/off power switch |
| Diagnostic LEDs                    | PROTECTION PRESENT (green), LINE FAULT (red) and LINE OK (green)                    |
| SURGE / NOISE SUPPRESSION          |                                                                                     |
| AC suppression joule rating        | 2850                                                                                |
| AC suppression response time       | NM = 0 ns. CM = <1 ns                                                               |
| Protection modes                   | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

|                                           |                                                                                            |
|-------------------------------------------|--------------------------------------------------------------------------------------------|
| Clamping voltage (RMS)                    | 140V                                                                                       |
| UL1449 let through rating                 | 330V - UL verified                                                                         |
| EMI / RFI filtering                       | Up to 40 dB40-80 dB                                                                        |
| <b>DATALINE SURGE SUPPRESSION</b>         |                                                                                            |
| Telephone/DSL Protection                  | Yes                                                                                        |
| Telephone/DSL Protection Details          | 1 line                                                                                     |
| Cable (Coax) Protection                   | Yes                                                                                        |
| Cable (Coax) Protection Details           | 2 line                                                                                     |
| Network (Ethernet) Protection             | No                                                                                         |
| <b>PHYSICAL</b>                           |                                                                                            |
| Shipping Dimensions (HWD/in)              | 3 x 11.5 x 7                                                                               |
| Shipping Dimensions (HWD/cm)              | 7.62 x 29.2 x 17.8                                                                         |
| Shipping weight (lbs)                     | 3.6                                                                                        |
| Shipping weight (kg)                      | 1.6                                                                                        |
| Unit Dimensions (HWD/in)                  | 2.5 x 9 x 3.5                                                                              |
| Unit Dimensions (HWD/cm)                  | 6.35 x 22.9 x 8.9                                                                          |
| Unit weight (lbs)                         | 2.8                                                                                        |
| Unit weight (kg)                          | 1.27                                                                                       |
| Material of construction                  | Metal                                                                                      |
| Integrated keyhole mounting tabs          | Keyhole mounting slots allow desk or wall mounting                                         |
| Housing Color                             | Black                                                                                      |
| Receptacle Color                          | Black                                                                                      |
| AC line cord color                        | Black                                                                                      |
| Style                                     | Strip                                                                                      |
| Outlets center to center measurement      | Distance between horizontal outlets = 39.45mm; Distance between vertical outlets = 39.30mm |
| Keyhole slot center to center measurement | Distance between horizontal tabs = 210.79mm; Distance between vertical tabs = 58.17mm      |
| <b>SPECIAL FEATURES</b>                   |                                                                                            |
| Appearance                                | Rugged all-metal corded strip format with high quality duplex receptacles                  |
| Right-Angle Plug                          | Yes                                                                                        |
| <b>CERTIFICATIONS</b>                     |                                                                                            |
| UL1449 3rd Edition (AC Suppression)       | UL1449                                                                                     |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                                               |                                                       |
|---------------------------------------------------------------|-------------------------------------------------------|
| UL1363 (Power Tap)                                            | UL1363UL1363                                          |
| UL497A (Communications)                                       | UL497A                                                |
| FCC Part 68 (Communications)                                  | FCC PFCC Part 68art 68                                |
| cUL / CSA (Canada)                                            | cULcUL                                                |
| Approvals                                                     | Exceeds IEEE 587 category A&B specifications          |
| <b>WARRANTY</b>                                               |                                                       |
| Product Warranty Period (Worldwide)                           | Lifetime limited warranty                             |
| Connected Equipment Insurance<br>(U.S., Canada & Puerto Rico) | \$250,000 <a href="#">Ultimate Lifetime Insurance</a> |

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Tripp Lite:](#)

[ISOBAR 6DBS](#)