

Semiconductor Fuseblocks

J70100 Series

700 Volt, 100 Amps



Catalog Symbol: J70100

Ampere Rating: 100A

Voltage Rating: 700Vac

Agency Information:

UL Recognized, Guide IZLT2, File E14853

Withstand Rating: 200,000 RMS Sym. Amps

For use with 22 x 58mm fuses

(FWP-40A22F, FWP-100A22F, etc.)


Materials: Thermoplastic

UL Flammability: 94VO

| Amps | Poles | Catalog Numbers | | |
|------|-------|------------------------------|-------------|---------------|
| | | Box Lug w/ Retaining Clip | Fig. No. | Wire Range |
| 100 | 1 | J70100-1CR | 1 | #2-14 CU/AL |
| | 2 | J70100-2CR | 2 | #2-14 CU/AL |
| | 3 | J70100-3CR | 3 | #2-14 CU/AL |

Dimensional Data

100A



The only controlled copy of this Data Sheet is the electronic read-only version located on the Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.