

K12 High Performance Key Switches

Features/Benefits

- Excellent tactile feel
- Wide choice of LED colors, travel and actuator forces
- High reliability / long life
- Sealed version available
- Designed for low-level switching
- Double stroke version available
- Detector version available

Typical Applications

- Automotive
- Off-road transportation
- Industrial electronics
- Computers & network equipment
- Joysticks



Construction:

FUNCTION: momentary
 DISTANCE BETWEEN BUTTON CENTERS:
 min. 11 (0.433) K12C = 13 (0.512)
 TERMINALS: PC pins, tinned
 MOUNTING: Locating pins; K12G and K12P additionally
 with snap-in housing

Mechanical

TOTAL TRAVEL: 1 mm, 1,5 mm, 2 mm
 SWITCHING TRAVEL: 0,6 mm*
 OPERATING FORCE: 1.5 N OD without snap-point as detector
 switch, 2.5 N, 3.5 N, 5 N, 3.5/7 N, 6/12 N. Additional
 operating force 7N, 9N and 20N, available on request.
 PROTECTION CLASS: K12C IP 67 (dust tight, protected against
 the effects of immersion in water; other versions IP 40)

* Additional switching travel (with pre-travel) available by request.

Packaging

Bulk in boxes of 250 pieces (version C or GO) or
 300 pieces (version A, AL, P or PL)

Electrical

SWITCHING POWER MIN./MAX.: 0.02mW/3 W
 SWITCHING VOLTAGE MIN./MAX.: 2 V DC / 30 V DC
 SWITCHING CURRENT MIN./MAX.: 10 mA /100 mA
 DIELECTRIC STRENGTH (50 Hz, 1 min): ≥ 500 V
 OPERATING LIFE with max. switching power: ≥ 10⁸ operations
 K12G & K12GO; operating life of second switch 5 x 10⁴ operations,
 operating life K12C and version with more than 6N (7N, 9N 20N)
 please consult factory.
 CONTACT RESISTANCE: Initial ≤ 50 mΩ
 INSULATION RESISTANCE: ≥ 10¹⁰ Ω
 BOUNCE TIME: ≤ 1 ms
 Operating speed 100 mm/s (3.94/s)

Environmental

OPERATING TEMPERATURE: -40°C to 85°C.
 STORAGE TEMPERATURE: -40°C to 95°C.


Process

SOLDERABILITY:
 Wave soldering, compatible with lead free soldering profile
 Hand soldering, 350°C

How To Order

Our easy build-a-switch concept allows you to mix and match options to create the switch you need. To order, select desired option from each category and place it in the appropriate box.

Note: Some of the configurations may not be available or could require some development.



* K12C – 1mm MAX

K12 with LED – 1.5 mm MAX


** K12G & K12GO version only

*** Additional operating force: 7N, 9N available on request


K12 High Performance Key Switches

SERIES


K12A without snap in




PCB LAYOUT, MOUNTING SIDE



K12AL



PCB LAYOUT, MOUNTING SIDE



\oplus	$1,1^{+0,05}$	2x	2x	center hole		
\oplus	$0,9 \pm 0,05$		2x	LED	$\phi 0,5 (0,020)$	Sn
		2x	2x	switch	$0,7 \times 0,2 (0,028 \times 0,081)$	Sn
Hole	ϕ	Without	with LED	Discription	Terminal Section	Surface

Key Switches




First Angle
Projection

Dimensions are shown: mm
Specifications and dimensions subject to change


K12 High Performance Key Switches

SERIES

K12P with snap in



PCB LAYOUT, MOUNTING SIDE




center of actuation area (notice LED)




Hole	Ø	Without LED	Description	Terminal Section	Surface
	1,7 (.069)	2x	snap-in		
	1,6 (.062)	1x	coding hole (L,M,N)		
	1,1 (.043)	2x	center hole		Sn
	0,9 (.035)	2x	switch	0.7 x 0.2 (.028 x .081)	Sn

K12PL



PCB LAYOUT, MOUNTING SIDE



center of actuation area (notice LED)




Hole	Ø	Without LED	Description	Terminal Section	Surface
	1,7 (.069)	2x	snap-in		
	1,6 (.062)	1x	coding hole (L,M,N)		
	1,1 (.043)	2x	center hole		Sn
	0,9 (.035)	2x	LED	m0.5 (.020)	Sn
	0,9 (.035)	2x	switch	0.7 x 0.2 (.028 x .081)	Sn



D

Key Switches



First Angle Projection




5 feb 15

Dimensions are shown: mm
Specifications and dimensions subject to change



K12 High Performance Key Switches

SERIES

K12C SEALED CONTACT WITH RUBBER CAP (IP 67)



PCB LAYOUT, MOUNTING SIDE



Hole	Ø	Without LED	Description	Terminal Section	Surface
	1,1 (.043)	2x	center hole		
	0,9 (.035)	2x	switch	0.7 x 0.2(.0275 x .0787)	Sn



D

Key Switches




First Angle
Projection

Dimensions are shown: mm
Specifications and dimensions subject to change




K12 High Performance Key Switches

SERIES


K12GO



PCB LAYOUT, MOUNTING SIDE



Hole	Ø	Without LED	Description	Terminal Section	Surface
	1,7 (.069)	2x	snap-in		
	1,6 (.062)	1x	code		
	0,9 (.035)		LED	m0.5 (.020)	Sn
		2x	switch 2	0.7 x 0.3 (.028 x .012)	Sn
		2x	switch 1	0.7 x 0.2 (.028 x .081)	Sn



Dimensions are shown: mm
Specifications and dimensions subject to change

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

C&K Components:

[K12ABK15N](#) [K12ABK1.52.5N](#) [K12GO NT 1.5 3.5-7N](#) [K12C BK 1 2.5N](#) [K12C 1 5N](#) [K12P BK 1.5 5N](#) [K12P BK 2 2.5N](#) [K12P BK 1 5N](#) [K12ABK11.5N0D](#) [K12ABK21.5N](#) [K12ABK22.5N](#) [K12ABK23.5N](#) [K12ALBU15NL328](#) [K12ALGN1.55NL306](#) [K12ALWH1.55NL302](#) [K12G0BK248.5N.5130CN](#) [K12G0LGN1.5612NL306](#) [K12G0LWH1.5612NL302](#) [K12PBK1.51.5N0D](#) [K12PBK1.51.5N0D1R](#) [K12PBK1.52.5N](#) [K12PBK1.53.5N](#) [K12PBK11.5N](#) [K12PBK13.5N1R](#) [K12PBK15N1R](#) [K12PL0G1.55NL315](#) [K12PL0G11.5N0DL315](#) [K12PLBU12.5NL328](#) [K12PLGN1.52.5NL306](#) [K12PLGN1.55NL306](#) [K12PLRD1.55NL352](#) [K12PLWH1.55NL302](#) [K12PLWH15NL302](#) [K12ABK12.5N1R](#) [K12ABK15N1R](#) [K12AGN1.52.5N](#) [K12AGY15N](#) [K12AGY1.52.5N](#) [K12ARD12.5N](#) [K12ARD15N](#) [K12ARD1.52.5N](#) [K12AYE12.5N](#) [K12AYE15N](#) [K12AYE1.52.5N](#) [K12AH11.5N](#) [K12AH12.5N](#) [K12AH1.52.5N](#) [K12AK11.5N](#) [K12AK12.5N](#) [K12AK1.51.5N](#) [K12AK1.55N](#) [K12ALGN15NL306](#) [K12ALRD15NL352](#) [K12ALYE15NL327](#) [K12DLYE12.5NL327](#) [K12G0BK1.53.57N](#) [K12G0BK1.5612N](#) [K12G0BK2612N.5](#) [K12PBK12.5N](#) [K12PBK21.5N0D](#) [K12PBK1.59N](#) [K12PD](#) [K12PL0G15NL315](#) [K12C12.5N](#) [K12DL YE 1 5N L327](#) [K12KKK BK](#) [K12D BK 1 5N](#) [K12P BK 1 3.5N](#) [K12PO BK 2 6N .8 200CN](#) [K12PL YE 1.5 5N L327](#)