

DESIGNATION

命名法

KX25-***P-LT-H1

H:WITH HOOK PIN
H:フックピン有り

(E X .)

A 4 X 1

PRODUCT CODE
製造コード

MATED CONDITION(REF.)

嵌合状態図(参考)



基板取付穴寸法(参考)

CONTACT AREA 接触部	GOLD(0.1 μ m MIN) OVER NICKEL N1上Au(0.1 μ m以上)めっき
TERMINAL AREA 端子部	TIN(REFLOW) OVER NICKEL N1上リフローSnめっき

NUMBER OF CONTACTS 芯数: N	D I M E N S I O N 寸 法			
	A	B	C	X
8 0	42.2	31.2	38.8	40.8
1 0 0	50.2	39.2	46.8	48.8
1 2 0	58.2	47.2	54.8	56.8
1 4 0	66.2	55.2	62.8	64.8
1 8 0	82.2	71.2	78.8	80.8

JAE CONNECTOR DIV. PROPRIETARY.
COPYRIGHT (C) 2004, JAPAN AVIATION ELECTRONICS INDUSTRY, LTD.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[JAE Electronics:](#)

[KX25-80P-LT-H1](#) [KX25-120P-LT-H1](#) [KX25-180P-LT-H1](#) [KX25-140P-LT-H1](#) [KX25-100P-LT-H1](#)