



REV.	DESCRIPTION	DATE	APPROVED
F	Corrected Board Thickness	04/01/14	J. C.
G	Engineering Release	04/01/14	J. C.
H	Removed BOM	08/09/16	J. C.



ORDERING INFORMATION

L24-ZESXXXXK

CORRELATED COLOR TEMPERATURE
IN KELVIN

Table 1: Assembly Configurations					
Part Number	LED P/N	Color	CCT (K)	Typical Luminous Flux (lm)	Philips Lumileds P/N Reference
L24-ZES2700K	BDL-1518	Warm White	2700	150	LXZ2-2780-5
L24-ZES3000K	BDL-1519	Warm White	3000	160	LXZ2-3080-5
L24-ZES4000K	BDL-1521	Neutral White	4000	190	LXZ2-4070
L24-ZES5000K	BDL-1522	Neutral White	5000	200	LXZ2-5070
L24-ZES5700K	BDL-1523	Cool White	5700	200	LXZ2-5770

STANDARD TOLERANCE (UNLESS OTHERWISE SPECIFIED)		 4 THOMAS, IRVINE, CA. 92618 TEL: (949) 951-8808 FAX: (949) 951-3974	
<u>DECIMALS</u>	<u>ANGULAR</u>		
.X ± .1	X° ± 1°		TITLE: L24 Starboard Light Engine
.XX ± .02			
.XXX ± .010			
DESIGNED: B. Oliver	DATE: 11/07/13	PART NO: L24-ZESXXXXK	
CHECKED: J. Chiang	DATE: 11/07/13	REVISION: H	
		CAGE CODE : 32559	SHEET # 1 OF 1
CAD GENERATED DOCUMENT, DO NOT MEASURE DRAWING.			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

BIVAR:

[L24-ZES3000K](#) [L24-ZES4000K](#) [L24-ZES5700K](#) [L24-ZES2700K](#) [L24-ZES5000K](#)