



Series L260 Lever Lok

RECOMMENDED GAP WIDTH

PCB + 7.62 mm (.300 in)

WEIGHT

1.17 g/cm (.105 oz/in)

MATERIALS AND FINISH

WEDGES, BODY, SHAFT

Material:
Aluminum Alloy 6061-T6 per per
ASTM-B221 or AMS-QQ-
A-200/8

Finish:
Black Anodize per MIL-A-8625,
Type II, Class 2

LEVER

Material:
Aluminum Alloy 6061-T6 per per
ASTM-B221 or AMS-QQ-
A-200/8

Finish:
Hard Black Anodize per MIL-
A-8625, Type III, Class 2

ADJUSTMENT SCREW


Material:
Stainless Steel per ASTM-A582
\\QQ-S-763


Finish:
Passivated per AMS2700

WASHERS

Material:
Front Washer: MPIF Standard 35 (no finish)
Rear Washer: ASTM-A240
Belleville Washers: ASTM-A666

Finish:
Passivate per AMS2700





CLAMPING FORCE ADJUSTMENT PROCEDURE

Lever-Lok is furnished unadjusted and will require the use of the following procedure to achieve proper clamping.

NOTE: Factory preset adjustment available on request. (See part number code)

1. Fasten Lever-Lok to Board Module Assembly
2. Insert Board Module Assembly into slot in cold plate
3. Actuate lever to locked/closed position
4. Tighten screw on end of shaft until wedges initially contact wall of cold plate slot, or slight insertion extraction drag is felt
5. Additionally tighten screw 2 full turns.

DO NOT EXCEED TWO (2) TURNS

6. Lever-Lok is now ready to use

Note: Factory adjustment of clamping force available on request. See P and P2 suffix option in Part Number Code table.

CLAMPING FORCE DATA

Direct force of assembly is approximately 556N (125lbs), when adjusted per recommended procedure.

Direct force of assembly is affected approximately as follows: 26.7N (6lbs) per each .025 (.001) variation of cold plate slot width, or 169N (38lbs) per each full turn of screw.

Part Number Code

Series L260 Card-Lok Five Piece

L260 - 3.80 TM2 -1 P

Suffix options

Assembly length in inches. Standard lengths range from 71.12 (2.80), 96.52 (3.80) and 121.9 (4.80) _____ length.xx

Other lengths available upon request

Mounting Options - M2 x 0.40 tapped holes _____ TM2

or choose from Mounting Option Table _____ see table

Lever Direction _____ -1

_____ -2

Factory Preset clamping force when expanded to 7.63 (.300)

556N (125lbs) _____ P

645N (145lbs) _____ P2

None _____ [blank]

Part Number Code Example:

L260-3.80TM2-1

Series L260 five piece lever actuated Card-Lok 96.52 (3.80) long with black anodized finish, -1 lever direction and no factory preset clamping load

MOUNTING METHOD TABLE

Code

Letter

Method

[blank]

2-56 tapped hole

"TM2"

M2 x 0.40 tapped hole

"TM2.5"

M2.5 x 0.45 tapped hole