# **LA5797MC**

#### **Monolithic Linear IC**

# **Charge Pump Step-up Power Supply for Variable Capacitance Diodes**



http://onsemi.com

#### Overview

The LA5797MC is a charge pump step-up power supply for Variable capacitance diodes.

#### **Features**

- By using charge pump, no coils are necessary.
- Time-base generator (140kHz) incorporated.
- Thermal shutdown circuit incorporated.

### **Specifications**

#### **Maximum Ratings** at $Ta = 25^{\circ}C$

Parameter	Symbol	Conditions	Ratings	Unit
Input voltage	V <sub>IN</sub> max		30	V
Allowable power dissipation	Pd max	Mounted on the specified board. *	0.75	W
Operating temperature	Topr		-25 to +90	°C
Storage temperature	Tstg		-40 to +150	°C
Junction temperature	Tjmax		150	°C

<sup>\*</sup> Specified board: 114.3mm × 76.1mm × 1.6mm, glass epoxy board.

Caution 1) Absolute maximum ratings represent the value which cannot be exceeded for any length of time.

Caution 2) Even when the device is used within the range of absolute maximum ratings, as a result of continuous usage under high temperature, high current, high voltage, or drastic temperature change, the reliability of the IC may be degraded. Please contact us for the further details.

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

### **Recommended Operating Conditions** at Ta = 25°C

Parameter	Symbol	Conditions	Ratings	Unit
Input voltage range	٧ <sub>IN</sub>		7.5 to 28	V

## **LA5797MC**

## **Electrical Characteristics** at Ta = 25°C


Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	Unit
Reference voltage	VFB	V <sub>IN</sub> = 15V, I <sub>O</sub> = 5mA	1.189	1.225	1.261	V
Switching frequency	f	V <sub>IN</sub> = 7.5V to 28V	112	140	168	kHz
Thermal shutdown operating temperature	TSD	Designed target value. *		165		°C
Thermal shutdown Hysteresis width	ΔTSD	Designed target value. *		15		°C


<sup>\*</sup> Design target value: No measurement made.

# **Package Dimensions**


unit: mm (typ)

3424







# **Pin Assignment**




# **Block Diagram**



# **Application Circuit Example** External circuit diagram (V<sub>CC</sub> = 24V)



External circuit diagram ( $V_{CC} = 15V$ )



Note : The IC is made active when the EN pin is pulled down to GND. The charge pump operation is stopped when the EN pin is pulled up to  $V_{\mbox{IN}}$ .

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equa

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ON Semiconductor: