




THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

|                                                |                                                                                                                                                |
|------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Material                                       | High Conductivity Seamless Copper Tube                                                                                                         |
| Plating                                        | Electro-Tin                                                                                                                                    |
| Wire Size                                      | 8 STR/FLEX                                                                                                                                     |
| Wire Type                                      | Stranded Copper: Class B & C, Compact, Class G, H, I, K, M, Locomotive                                                                         |
| Wire Strip Length                              | 1/2 in.                                                                                                                                        |
| Stud Size                                      | 1/4 in.                                                                                                                                        |
| UL Listed Wire Connector                       | Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts. |
| UL Temperature Rating                          | 90° C                                                                                                                                          |
| C.S.A Certified Wire Connector                 | Yes                                                                                                                                            |
| Panduit Color Code on Barrel                   | RED                                                                                                                                            |
| Panduit Die Index No. on Barrel                | P21                                                                                                                                            |
| Alternate Industry Die Index No. ( ) on Barrel | N/A                                                                                                                                            |



LISTED  
Wire Connector



| 02  | 7/03 | TLCO | TLCO | REMOVED PANDUIT FROM BARREL MARKINGS | 10918 |
|-----|------|------|------|--------------------------------------|-------|
| REV | DATE | BY   | CHK  | DESCRIPTION                          | ECN   |

**PANDUIT CORP. TINLEY PARK, ILLINOIS**

LCAX8-14F-L  
Copper Lug - One-Hole, Standard Flex Barrel, 90° Angle Tongue

SCALE N/A DRAWING NO / CAD FILE LCAX8-14F-CUST

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

[LCAX8-14F-L](#)