

[GO](#)[BUY NOW](#)[DESIGN / INSTALL](#)

LCMB25-8-L

One-hole, metric conductor, long barrel, 25mm² 2r, 16mm² class 5F/6F, M8 stud hole.

[Specs](#)[Documents](#)[★ Add to Favorites](#)[🛒 Add to BOM](#)

Std. Pkg. Qty.	50
Conductor Material	Copper
Product Type	Tin-Plated Copper Compression Connectors - Metric Lugs
Angle	Straight
Barrel Type	Long Barrel Length without Inspection Window
Copper Conductor Size Class 2 (mm ²)	25
Copper Conductor Size Class 5F (mm ²)	16
Copper Conductor Size Class 6F (mm ²)	16
Stud Hole Size (mm)	M8
Barrel I.D. (mm)	6.9
Barrel Length (mm)	26.7
Length (mm)	48.7
Palm Width (mm)	15.5
Stud Set Back (mm)	8
Tongue Thickness (mm)	1.6
Wrench Clearance (mm)	10
Panduit Die Index No.	P29
Panduit Indenter Die Index No.	—
Panduit Nest Die Index No.	—
Wire Strip Length (mm)	28.3
American Bureau Shipping Approved	Yes
CE Compliant	Yes
CSA Certified	C22.2 No. 65-13
Standards	Meets EN 61238-1:2003/IEC 61238-1:2003 Class B
Tin-Plating Meets ASTM B545-97, Class C	320µ in (8µ m)
UL Listed	486A-486B File #E52164
UL and CSA Temperature Rating	90° C
UL and CSA Voltage Rating	35kV
Part Number Series	LCMB
Barrel Style	Long
Part Features	Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 V
Plating Type	Tin Plated
RoHS Compliancy Status	Compliant
Min. Order Qty.	50.0000