## UNCONTROLLED DOCUMENT

(X)


PART NUMBER


LDS-A6006RI


E.C.N. NUMBER AND REVISION COMMENTS


DATE

REV.









ELECTRO-OPTICAL CH	IARACTEF	RISTICS TA=25°	'C	$I_f=10mA$	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		660 (RED)		nm	
FORWARD VOLTAGE		1.7	2.3	$V_{f}$	
REVERSE VOLTAGE	5.0			$V_r$	I <sub>r</sub> =100μΑ
AXIAL INTENSITY		13,000		μcd	$I_f = 10mA$
EMITTED COLOR:	RED				
FACE COLOR:	GRAY				
SEGMENT COLOR:	MILKY	WHITE DIFFUS	ED		
-	•				

## LIMITS OF SAFE OPERATION AT 25°C PER CHIP

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	- 1.2	mW/*C
OPERATING, STORAGE TEMP.	- 40 TO +85	•C
SOLDERING TEMP.	+ 260	•C
2.0mm FROM BODY		3 SEC. MAX

\* t<10µS

5.10 COMMON ANODE D

REPLACES PART #:LDS-A606RI

## \*UNLESS OTHERWISE SPECIFIED TOLERANCE IS ±0.25mm (±0.010")

REV.

PART NUMBER LDS-A6006RI

0.60" SINGLE DIGIT, SEVEN SEGMENT DISPLAY, 660nm RED CHIPS WITH GRAY FACE, MILKY WHITE DIFFUSED SEGMENTS, COMMON ANODE.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

LUME	K
INCORPORATED	

290 E. HELLEN ROAD PALATINE, ILLINOIS 60067 PHONE: 1-847-359-2790 WEB: HTTP://WWW.LUMEX.COM

APPROVED BY: DATE: 1-25-99 CHECKED BY: DRAWN BY: PAGE: 1 OF 1 SCALE: N/A SS/BC

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

<u>Lumex</u>:

LDS-A6006RI