

### **Cable Limiters**

#### 600 Volts AC



Description			Catalog Number	
Tuna	Termination	Cable Size	Cable Type	
Type			Copper	Aluminum
1		4/0	LFCL4/0C1	LFCL4/0A1
		250MCM	LFCL250C1	LFCL250A1
		350MCM	LFCL350C1	LFCL350A1
		500MCM	LFCL500C1	LFCL500A1
	Cable to Cable	750MCM	LFCL750C1	LFCL750A1
3	5	4/0	LFCL4/0C3	LFCL4/0A3
		250MCM	LFCL250C3	LFCL250A3
		350MCM	LFCL350C3	LFCL350A3
	Cable to Offset Bus	500MCM	LFCL500C3	LFCL500A3
		750MCM	LFCL750C3	LFCL750A3
5	Straight Bus to Offset Bus	4/0	LFCL4/0C5	_
		250MCM	LFCL250C5	_
		350MCM	LFCL350C5	-
		500MCM	LFCL500C5	_
		750MCM	LFCL750C5	_
6	5	4/0	LFCL4/0C6	LFCL4/0A6
		250MCM	LFCL250C6	LFCL250A6
		350MCM	LFCL350C6	LFCL350A6
		500MCM	LFCL500C6	LFCL500A6
	Mole to Cable	750MCM	LFCL750C6	LFCL750A6
8	5	4/0	LFCL4/0C8	_
		250MCM	LFCL250C8	_
		350MCM	LFCL350C8	_
	Mole to Offset	500MCM	LFCL500C8	_
	Bus	750MCM	LFCL750C8	_

Cable limiters are fusible devices that provide very fast short-circuit protection, primarily to faulted cables, but also to other conductors such as busway. Cable limiters do not have an ampere rating, and cannot be used to provide overload protection. They are instead selected by cable size; for example, a 500 kcmil cable requires a 500 kcmil cable limiter. Their main use is to isolate faulted cables in circuits containing three or more parallel conductors per phase. They may be installed on the line side of the main service to provide short-circuit protection to the service conductors. This is especially important when service conductors are tapped from large low voltage networks or from large low impedance transformers.

Cable limiters have terminals which permit them to be installed in a variety of equipment. The most common configuration is the offset blade on one end and the crimp terminal on the other end. This permits the limiter to replace a cable terminal (lug).

## **Applications**

Service entrance conductors

Between transformer or network bus and busway terminal boxes Large feeders with three or more conductors per phase

#### **Features**

- Current-limiting characteristics provide protection to conductor insulation and reduce damage when faults occur.
- Properly applied cable limiters may permit the use of equipment with reduced withstand ratings
- Wide variety of terminations and cable ratings permit use in almost every situation.


#### **Specifications**

Voltage Rating: 600 volts AC Interrupting Rating: 200,000 Amperes

**Cable Size Range:** 4/0 - 750MCM Copper or Aluminum

Note: For Type 5 and Type 8 Aluminum cable limiters, use the Copper Type C5 and C8.

## **Ordering Information**



# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Littelfuse:

LFCL0500ZA6 LFCL0500ZA1 LFCL0500ZA3 LFCL0500ZC6 LFCL0500ZC8 LFCL0500ZC5 LFCL0500ZC1 LFCL0500ZC3 LFCL0250ZA1 LFCL0250ZA3 LFCL0250ZA6 LFCL0250ZC1 LFCL0250ZC5 LFCL0250ZC3 LFCL0250ZC8 LFCL0250ZC6 LFCL0750ZA6 LFCL0750ZA1 LFCL0750ZA3 LFCL0750ZC3 LFCL0750ZC1 LFCL0750ZC5 LFCL0750ZC6 LFCL0750ZC8 LFCL04/0ZC3 LFCL04/0ZC5 LFCL04/0ZC1 LFCL04/0ZC6 LFCL04/0ZC6 LFCL04/0ZC8 LFCL04/0ZA3 LFCL04/0ZA1 LFCL04/0ZA6 LFCL0350ZC6 LFCL0350ZC8 LFCL0350ZC5 LFCL0350ZC5 LFCL0350ZC1 LFCL0350ZC3 LFCL0350ZA1 LFCL0350ZA3