Panasonic Industrial

Part Number: LR6XWA


(Replaces Panasonic part number AM-3PI)

Alkaline-Zinc/Manganese Dioxide



Industry Standard Dimensions mm (inches)

Dimensions Comply with ANSI and IEC Standards



Dimensions	Millimeters	Inches
A Max	50.5	1.988
B Min	49.5	1.949
C Min	7.0	0.276
F Max	5.5	0.217
G Min	1.0	0.039
OD Max	14.5	0.571
OD Min	13.5	0.531

Medical

Contractors

- **Batteries for every application and industry including:** Hotel/Motel/Restaurant
- Communications
 Government/Municipality
 HVAC
 - Janitorial/Sanitation
- Manufacturing Military/Defense
- Transportation

 - Power Plants
 - Security

Specifications

Chemical System:	Alkaline-Zinc/Manganese Dioxide (Zn/MnO2)	
Designation:	ANSI-15A, IEC-LR6	
Nominal Voltage:	1.5V	
Operating Temperature Range:	-20°C to 54°C (-4°F to 130°F)	
Typical Weight:	23 grams (0.8 oz.)	
Typical Volume:	8.1 cm³ (0.5 in.³)	
Terminals:	Cap and base	
Shelf Life:	7 years (80% Capacity)	
Heavy Metals Content:	No added Mercury, Cadmium or Lead	

Important Notice: This data sheet contains typical information specific to products manufactured at the time of its publication.












Panasonic Industrial


Part Number: LR6XWA (Replaces Panasonic part number AM-3PI)

Alkaline-Zinc/Manganese Dioxide


Typical Discharge Characteristics with Constant Current at 20°C




Typical Discharge Characteristics with Constant Resistance at 20°C





Typical Temperature Characteristics 0.9 Volts Cutoff Voltage




IEC/ANSI Standard Tests @ 20°C









This information is generally typical and is not intended to make or imply any representation, guarantee or warranty with respect to any cells and batteries. Cell and battery designs/specifications are subject to modification without notice. Cell/battery performance and service life depends on the operating temperature, cut-off voltage and load applied to cell/battery in a specific application. It is the responsibility of each user to ensure that each cell/battery application is adequately designed safe and compatible with all conditions encountered during use and in conformance with existing standards and requirements. Contact Panasonic for the latest information.

©2009 Panasonic Energy Corporation of America. All rights reserved. All reproductions prohibited without proper authorization. Characteristics and specifications subject to change without prior notification.

Panasonic ideas for life

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panasonic:

LR6XWA LR6XWA/2SB LR6XWA/C LR6XWA/B LR6XWA/B2 LR6XWA/B24 LR6XWA/3SB