


Double-Pole Rocker Switch

LR Series



Features

- Single-throw and double-throw options
- Lighted and non-lighted options
- Industry standard mounting dimensions
- Mechanical life: min. 100,000 operations

Electrical Ratings				
Switch Series	EN61058 Rating	UL1054 Rating	Electrical Life at Rated Load	
			According to VDE (Min. Operations)	According to UL (Min. Operations)
LR	10(4)A, 250V~T125/55	10A 125VAC 1/4HP, 8A 250VAC; 1/4HP	10,000	6,000

Electrical Specifications		Material Specifications	
Ratings:	10A 125VAC 1/4HP 8A 250VAC 1/4HP (cULus) 10(4)A, 250V~ T125/55 (VDE)	Actuator: (non-lighted) (lighted)	Nylon 66 94V-2 Polycarbonate
Dielectric Strength:	1000VAC for 1 minute	Base:	Nylon 66 94V-2
Insulation Resistance:	100M ohms min at 500VDC	Spring:	Steel Wire
Initial Contact Resistance:	0.020 ohms max	Contacts:	Silver Alloy
Temperature Range:	-20°C to + 65°C	Movable Arm:	Copper Alloy
		Terminals:	Tin-Plated Copper Alloy




RoHS Compliant
UL File No: E23301

Specifications subject to change without notice.



LR Series

Dimensions (inches)



Z = Panel Thickness

Recommended Panel Cut-Out Dimensions

inches (mm)

Dim. Z	Dim. X	Dim. Y
0.030 to 0.049 (0.75 to 1.25)	0.752 (19.10)	0.508 (12.90)
0.049 to 0.079 (1.25 to 2.00)	0.760 (19.30)	0.508 (12.90)
0.079 to 0.118 (2.00 to 3.00)	0.775 (19.69)	0.508 (12.90)

Ordering Information

The diagram illustrates the relationship between various product codes and their specifications. It includes several tables and arrows indicating how these codes relate to the main product code 'A'.

LR Series

Code	Circuitry
2	Single Pole
3	Double Pole

A Contact Rating

A	10A 125VAC 1/4 HP 8A 250VAC 1/4HP cULus 10(4)A 250V ~ T125/55 VDE
---	---

Code Switch Function

Code	Switch Function
2	On - Off

H Code Actuator Type

Code	Actuator Type
2	Curved

F Code Actuator Marking

Code	Actuator Marking
B	Blank
D	Q
E	O
F	O
G	.

B Code Housing Color

B	Black
W	White
Y	Grey
E	Charcoal Grey

B Code Actuator Color

A	Amber
B	Black
G	Green
R	Red
W	White
Y	Grey
E	Charcoal Grey

N Code Lighted

N	Non-Lighted
L	Lighted (Bulb 125VAC)
E	Lighted (Bulb 250VAC)
F	Lighted (5VDC Incandescent)
G	Lighted (6VDC Incandescent)
H	Lighted (12VDC Incandescent)

Code Terminal type inches (mm)

H	0.187 (4.8) QC
L	PC Thru-Hole Right Angle
M	PC Thru-Hole Straight
B	PC Thru-Hole Left Angle

Code Splashproof

N	No Rocker Boot
S	Rocker Boot

Examples of Common Part Numbers and Descriptions inches (mm)

Part Number	Circuitry	Switch Function	Terminal Type	Actuator/ Housing Color	Legend Marking
LRA22H2FBBNN		On – Off	0.187 (4.8) Quick-Connect	Black/Black	
LRA32H2FBBNN		On – Off	0.187 (4.8) Quick-Connect	Black/Black	
LRA22H2BBBNN		On – Off	0.187 (4.8) Quick-Connect	Black/Black	
LRA32H2BBBNN		On – Off	0.187 (4.8) Quick-Connect	Black/Black	
LRA22H2BBBRLN		On – Off/Lighted	0.187 (4.8) Quick-Connect	Red/Black	
LRA32H2BBBRLN		On – Off/Lighted	0.187 (4.8) Quick-Connect	Red/Black	

Boat #0015-0644

Contact

Call, fax or visit our
Website for more information.

ZF Electronics Corporation
11200 88th Avenue
Pleasant Prairie, WI 53158

Phone: 262.942.6500
Web: www.cherrycorp.com
Email: cep_sales@zf.com
Fax: 262.942.6566

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice.

Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2007 ZF Electronics Corporation

Last Updated: 10/01/12

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ZF Electronics:

[LRA22H2BBRLN](#) [LRA22H2FBBNN](#) [LRA22H2FBALN](#) [LRA22H2FWWNN](#) [LRA22H2FBRLN](#) [LRA22H2FYYYN](#)
[LRA22H2FBMLN](#) [LRA32H2BBMLN](#) [LRA22H2FBGLN](#) [LRA32H2BBALN](#) [LRA32H2BBBNN](#) [LRA32H2BBGLN](#)
[LRA22H2DBBNN](#) [LRA22H2FBRNN](#) [LRA22H2BBGLN](#) [LRA22H2BBALN](#) [LRA22H2BBMLN](#) [LRA22H2BBBNN](#)
[LRA22H2BBREN](#) [LRA32H2FBGLN](#) [LRA32L2FWWNN](#) [LRA32H2DBBNN](#) [LRA32H2FBMLN](#) [LRA32H2FBRLN](#)
[LRA32H2BBRLN](#) [LRA32H2FBALN](#) [LRA32H2FBBNN](#) [LRA32L2EBBNN](#)