

[→ Honeywell.com](#) [→ Automation & Control Solutions](#)[HOME](#)[ABOUT US](#)[KEY INDUSTRIES SERVED](#)[PRODUCTS & INFORMATION](#)[NEWS & EVENTS](#)[SALES & SUPPORT](#)[LOGIN](#)

## Honeywell Sensing and Control

Search



### narrow your search

#### Products

- Controls Monitoring and Lighting (286)
- Machine Safety (1727)
- Sensors (6165)
- Switches (9781)
- Wireless (45)

#### Technology

- Control and Instrumentation (890)
- Electromechanical (9307)
- Magnetic (541)
- Platinum thin film (56)
- Thick Film (1372)
- More...

### new products

#### New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site  
WGLA and WPMM  
XYR6000™

[find out more](#)

### white papers

Wireless Switches Offer  
Unlimited Benefit  
Basic Switches Are Not Created  
Equal  
Applying Precision Switches  
Sensors for Medical Devices  
New Ways to Measure Torque  
Choosing Safety Switches  
Specifying Hour Meters

### Need help?

[Click here to contact us](#)

#### LSA6B-1D

( Home : Products : Switches » MICRO SWITCH™ Limit Switches » MICRO SWITCH™ Heavy-Duty Limit Switches » HDLS )



Series HDLS Plug-in: Side Rotary; 2NC 2NO DPDT Snap Action;  
0.5 in - 14NPT conduit

Actual product appearance  
may vary.  
[click here to download Hi-Res image](#)

[Sales & Service](#)[Distributor Inventory](#)[Overview](#) [Specs](#) [Documentation](#) [Application Notes](#)

#### Product Specifications

|                                |                                                                                      |
|--------------------------------|--------------------------------------------------------------------------------------|
| Availability                   | Global                                                                               |
| Operating Force (OF)           | 0,45 N m [4 in lb] max.                                                              |
| Pretravel (PT)                 | 15° max.                                                                             |
| Overtravel (OT)                | 60° min.                                                                             |
| Differential Travel (DT)       | 7° max.                                                                              |
| Product Type                   | MICRO SWITCH™ Heavy-Duty Limit Switches                                              |
| Actuator                       | Side Rotary                                                                          |
| Lever Type                     | 1.5 in Fixed Length Lever with back mounted Steel Roller (.75 in dia. x .25 in wide) |
| Circuitry                      | 2NC 2NO DPDT Snap Action, Double-Break                                               |
| Ampere Rating                  | 10 A (Thermal)                                                                       |
| Supply Voltage                 | 600 Vac and 250 Vdc max.                                                             |
| Housing Material               | Zinc Die-Cast                                                                        |
| Termination Type               | 0.5 in - 14NPT Conduit                                                               |
| Housing Type                   | HDLS Plug-in                                                                         |
| Series Name                    | HDLS                                                                                 |
| Sealing                        | NEMA 1, 3, 4, 4X, 6, 6P, 12, 13                                                      |
| UL File #                      | E37138                                                                               |
| Operating Temperature          | -12 °C to 121 °C [10 °F to 250 °F]                                                   |
| Comment                        | Lever Included                                                                       |
| Agency Approvals and Standards | UL, CE, CSA, CCC, EN60947-1, EN60947-5-1                                             |
| UNSPSC Code                    | 302119                                                                               |
| UNSPSC Commodity               | 302119 Switches and controls and relays                                              |
| Sealed                         | Industrial                                                                           |

### contacts

Customer Service  
Technical Support  
Global Sales & Service  
View Site Demo  
Site Comments?

### meet dr. larry

**VIDEO** - Dr. Larry Goldstein explains our newest and best technologies.



Meet Dr. Larry

### my links

Login to iCOM  
Login to Rep/AD Portal  
Login to Digital University

### News Center

Honeywell Introduces  
TruStability® NSC Series,  
Uncompensated / Unamplified  
Board Mount Pressure Sensors  
  
HONEYWELL EXPANDS ITS  
LIMITLESS™ PLATFORM WITH  
THE LAUNCH OF ITS  
GLOBALLY AVAILABLE  
INDUSTRIAL WIRELESS  
RECEIVER  
  
HONEYWELL EXTENDS ITS  
TRUSTABILITY® PRESSURE  
SENSOR PRODUCT LINE WITH  
A SINGLE SIDE LIQUID MEDIA  
OPTION  
  
HONEYWELL ADDS NEW 100°  
AND 180° ARC  
CONFIGURATIONS TO ITS  
SMART POSITION SENSOR  
PORTFOLIO  
  
HONEYWELL INTRODUCES  
ITS HAWK™ RESOLVERS 1-  
INCH SERIES, FULLY HOUSED  
CONFIGURATION  
  
HONEYWELL INTRODUCES  
MICROPOWER OMNIPOLAR  
DIGITAL HALL-EFFECT  
SENSOR ICS WITH LOW  
SUPPLY VOLTAGE AND ULTRA  
LOW TYPICAL CURRENT

**MICRO SWITCH  
Anniversary site**

[Terms & Conditions](#) | [Privacy Statement](#) | [Site Map](#)