

166-90388

Article Number: 166-90388

Description: Liquid-Tight Metallic Conduit, Flexible, 0.50" (20mm) Dia, Galvanized Steel w/PVC Cover, Gray, 82ft/Reel



Base Data	
Local Order Number	LTP20G-25M
Type	LTS0508-25M
Color	Gray (GY)
Features and benefits	<ul style="list-style-type: none"> • Flexible metallic conduit provides liquid-tight performance to IP66 + IP67 + IP68 + IP69 when used with LTP or LTPUL series fittings. • Helically wound (spiral) galvanized steel core with an interlocking design delivers high degree of compression strength and impact resistance. • Smooth PVC cover resists oil and grease and will not wrinkle when conduit is bent; also resistant to acids. • UV-resistant (black), suitable for outdoor use. • Manufactured to UL360 requirements.
Quantity Per	reel
Brand Family	HelaGuard
Product Description	A flexible, liquid-tight galvanized steel conduit with a smooth oil resistant PVC coating. LTP series is a general purpose, non-UL rated liquid-tight conduit used in applications that require movement, vibration and bending. Use with LTP or LTPUL series metallic fittings for IP66 + IP67 + IP68 + IP69 ratings. Designed for applications where a UL listing or CSA certification is not required but where a need still exists for a flexible metal conduit to protect wires against impact and exposure to oils and chemicals. My be used in hazardous locations when accompanied with LTPUL or EXD metallic fittings.
GLOBAL PART NAME (auto set)	LTS0508-25M-GS/PVC-GY
Technical Description	Manufacturer Reference Number: LTP20G-25M
Short Description	Liquid-Tight Metallic Conduit, Flexible, 0.50" (20mm) Dia, Galvanized Steel w/PVC Cover, Gray, 82ft/Reel
Product Dimensions	
Length L (Imperial)	82.0ft
Length L (Metric)	25.0m
Reel Length (imperial)	82.0ft
Diameter D (imperial)	0.63"
Diameter D (metric)	16.0mm
Outside Diameter D (imperial)	0.83"
Outside Diameter OD (metric)	21.1mm

166-90388

HellermannTyton

Product Dimensions	Nominal Diameter (Imperial)	1/2"
	Nominal Diameter (Metric)	20.0mm
	Inside Bend Radius (Metric)	65mm
Material and Specifications		
	Material	Polyvinylchloride (PVC) Galvanised Steel (GS)
	Material Shortcut	PVC GS
	Flammability	Self-Extinguishing according to EN IEC 61386-1
	Halogenfree	No
	Operating Temperature	-4°F to +221°F (-20°C to +105°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	82ft
	Package Quantity (Metric)	25.0m
	Weight (imperial)	22.4lbs
	Weight (Metric)	10.18kg