


Capacitor, ceramic, 120 pF, +/-10% Tol, 200V, BX, Lead Spacing=0.2"



## **Dimensions (in)**

## **Specifications**

| ID | Dimension | Tolerance     | Manufacturer:            | KEMET          |
|----|-----------|---------------|--------------------------|----------------|
| w  | 0.09      | +/-0.01       | Capacitance:             | 120 pF         |
| Н  | 0.19      | +/-0.01       | Lead Spacing:            | 0.2"           |
| L  | 0.19      | +/-0.01       | Voltage:                 | 200V           |
| s  | 0.2       | +/-0.03       | Temperature Coefficient: | BX             |
| LL | 1.25      | min           | Tolerance:               | +/-10%         |
| F  | 0.025     | +0.004/-0.002 | Body Type:               | Radial Molded  |
| G  | 0.026     | min           | Lead Type:               | Standard Leads |
|    |           |               | Lead Form:               | Hockey Stick   |
|    |           |               | Package Kind:            | Bulk           |
|    |           |               | Package Type:            | Bag            |
|    |           |               | Package Quantity:        | 100            |
|    |           |               |                          |                |

## Notes:

- -Note A: Center line of the leads will be within 0.03 in [0.76 mm] of the center line of the body.
- -Lead length shown is for parts supplied in bulk. See packaging specifications for lead lengths when not provided in bulk

