








Datamate – Special Contacts

COAX

DATAMATE MIX-TEK

| FEMALE | | | MALE | | |
|-------------------|--|---|-------------------|---|---|
| 301 or 302 |  | Vertical PC Tail 301 = 3.00mm tail 302 = 4.50mm tail | 311 or 312 |  | Vertical PC Tail 311 = 3.00mm tail 312 = 4.50mm tail |
| | | | 313 or 314 |  | Horizontal PC Tail 313 = 3.00mm tail 314 = 4.50mm tail |
| 305 306 307 |  | Straight Crimp 305 = Ø2.00mm cable 306 = Ø2.40mm cable 307 = Ø2.70mm cable | 315 316 317 |  | Straight Crimp 315 = Ø2.00mm cable 316 = Ø2.40mm cable 317 = Ø2.70mm cable |
| 308 or 309 |  | 90° Crimp 308 = Ø2.00mm cable 309 = Ø2.70mm cable | 318 or 319 |  | 90° Crimp 318 = Ø2.00mm cable 319 = Ø2.70mm cable |

| CABLE SIZE | CABLE TYPE | CONTACTS |
|---------------|---------------|----------|
| Ø2.00mm cable | RG 178 | 305 315 |
| | | 308 318 |
| Ø2.40mm cable | PTFE Cellular | 306 316 |
| Ø2.70mm cable | RG 174 | 307 317 |
| | RG 179 | |
| | RG 316 | 309 319 |