



Datasheet for part number M83513/03-A07C

|   |
|---|
| Our Catalog Part Number: M83513/03-A07C                                       |
| Our Global Manufacturing Part Number: 154170-0007                             |
| Brand: Cannon Product Category: Micro Product Line: Micros Series: M83513-1-4 |

| Product Datasheet               |  |
|---------------------------------|--|
| Series                          | Micro D Metal Shell - 0.050 inch spacing                 |
| Slash Sheet                     | Plug, Connector  |
| Arrangement                     | 9 Contact  |
| Contact Typ                     | Crimp  |
| Contact Material                | gold plated copper alloy                                 |
| Contact Resistance              | 8 milliohms max.   |
| Wire Length                     | 0.5 inch long, #25AWG, type S per QQ-W-W-343, Tin Plated |
| Shell Material                  | Aluminum   |
| Shell Finish                    | Cadmium / Yellow chromate over nickel                    |
| Insulator                       | LCP  |
| Current Rating                  | 3 A max.   |
| Dielectric Withstanding Voltage | 600 VAC at sea level<br>150 VAC at 70,00' altitude       |
| Insulator Resistance            | 5000 megohms min.  |
| Thermal Shock                   | -55°/+125°   |
| Physical Shock                  | 50 G's, 3 axes, 6 milisecond duration sawtooth pulse     |
| Vibration                       | 20G's, 10-2000 Hz. 12 hours                              |
| Durability                      | 500 cycles of mating and unmating, 500 CPH max.          |
| Moisture Resistance             | Insulator resistance > 100 megohms                       |
| SaltSpray                       | 48 hours   |