LED Lamp





MC-T8-120

Line-Up:

Part Number	Watts (W)	Light Output (Im)	Dimension (mm)	Light Color (K)	Beam Angle (Degree)
MC-T8-120-20W-U-M-CW-00	19 ±1	1,850 ±10%	1,212.2 × 26	6,000	120
MC-T8-120-20W-U-M-NW-00	1911	1,700 ±10%	1,212.2 × 26	-	120

Technical Specifications:

Item	Test Conditions	Min.	Тур.	Max.
Input Voltage (V rms)	AC	90	220	277
Input Current (A rms)	AC(220V)		0.09	
Input Power (W rms)	AC(AII)		20	
Input Frequency (Hz)	AC		50Hz/60Hz	
Power Factor (PF)	AC(AII)		>0.9	
Output Voltage (V)	DC	39	39.5	40
Output Current (A)	DC	0.42	0.435	0.45
Output Power (W)	DC	16.38	17.1825	18

Environmental Requirements:

Specifications	Values
Operational Temperature Range	-20°C to 40°C
Preservation Temperature Range	-20°C to 90°C
Operational Humidity Range	95%Rh or below (@-20°C to 40°C)
Installation Area	Indoor (Counter, Residential, Commercial, etc)

Drawing:



www.element14.com www.farnell.com www.newark.com



LED Lamp



MC-T8-150

Line-Up:

Part Number	Watts (W)	Light Output (Im)	Dimension (mm)	Light Color (K)	Beam Angle (Degree)
MC-T8-150-33W-F-M-CW-00	33 ±10%	2840 ±10%	1,513 × ¢25.6	6,000	120
MC-T8-150-33W-F-M-NW-00	33 ± 10%	2,720 ±10%	1,513 × ¢25.6	-	120

Technical Specifications:

Item	Test Conditions	Min.	Тур.	Max.
Input Voltage (V rms)	AC	100	200	240
Input Current (A rms)	AC(220V)		0.15	
Input Power (W rms)	AC(All)		33	
Input Frequency (Hz)	AC		50Hz/60Hz	
Power Factor (PF)	AC(All)		>0.9	
Output Voltage (V)	DC	36	37.8	39.6
Output Current (A)	DC	740	750	760
Output Power (W)	DC	26.6	28.3	30.1

Environmental Requirements:

Specifications	Values
Operational Temperature Range	-20°C to 40°C
Preservation Temperature Range	-20°C to 90°C
Operational Humidity Range	95%Rh or below (@-20°C to 40°C)
Installation Area	Indoor (Counter, Residential, Commercial, etc)

Drawing:



Dimensions: Inches

www.element14.com www.farnell.com www.newark.com



LED Lamp



Part Number Table

Description	Part Number		
LED Lamp T8-120	MC-T8-120-20W-U-M-CW-00		
	MC-T8-120-20W-U-M-NW-00		
LED Lamp T9 150	MC-T8-150-33W-F-M-CW-00		
LED Lamp T8-150	MC-T8-150-33W-F-M-NW-00		

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.



