


ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION. WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

REVISIONS				DOC. NO. SPC-FD05 + Effectives 7/8/02 + DCP No. 1398					
DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE	
2022	Α	RELEASED	ИL	1/07/09	MWL	1/07/09	JWM	1/07/09	





NOTE:

- 1. MAXIMUM ELECTRIC CURREENT: A.W.G. | 22 | 20 | 18 | 16 AMP. | 9 | 12 | 17 | 18 2. WIRE RANGE: 22-16 A.W.G (0.5-1.5 mm ²)
- 3. SURFACE TREATMENT: TIN PLATED
- 4. THICKNESS: 0.80 mm

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED
HEREIN ARE BASED LIPON INFORMATION AND/OR TESTS WE
BELIEVE TO BE ACCURATE AND RELIABLE. SINCE
CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE
USER SHALL DETERMINE THE SUITABLITY OF THE PRODUCT
FOR THE INTENDED USE AND ASSUME ALL RISK AND
LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

ø3.3±0.20 -

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE
FOR REFERENCE
PURPOSES ONLY.

TOLERANCES:

DRAWN BY: DATE:		DRAW	ING TITLE:						
Jason Nash 1/07/09					Non-Insulated E	3utt 1	Connecto	r	
CHECKED BY:	DATE:	SIZE	IZE DWG. NO.		ELEC	REV			
Jeff McVicker	1/07/09] 🛕	MC29368		29368	34P2137.dwg			A
APPROVED BY:	DATE:								
Jeff McVicker	1/07/09	SCALE: NTS		U.O.M.: INCHES [mm]		SHEET: 1 (- 1	