




DELTA P/N : MPT1040-M1 Series

Mechanical dimensions



Unit : mm		
A'	11.15 ± 0.35	For R15~1R5
	10.85 ± 0.35	For 2R2~5R6
A	10 ± 0.3	
B	3.8 ± 0.2	
C	2.0 ± 0.5	
C'	2.5 ± 0.1	
D	3.0 ± 0.5	
D'	5.0 ± 0.2	
E	0~0.15	
F	4.1	
G	5.4	
H	13.6	

Electrical Characteristics

Part No.	Lo @0A (uH) ± 20%	Ir(Adc)	Isat(Adc)	DCR (mΩ)	
				TYP.	MAX
MPT1040-R15M1	0.15	40.0	75.0	0.5	0.65
MPT1040-R19M1	0.19	38.0	60.0	0.7	0.8
MPT1040-R22M1	0.22	35.0	60.0	0.9	1.0
MPT1040-R36M1	0.36	30.0	60.0	1.05	1.2
MPT1040-R39M1	0.39	30.0	60.0	1.10	1.3
MPT1040-R41M1	0.41	30.0	60.0	1.1	1.3
MPT1040-R45M1	0.45	29.0	45.0	1.1	1.3
MPT1040-R47M1	0.47	26.0	40.0	1.6	1.8
MPT1040-R56M1	0.56	25.0	40.0	1.6	1.8
MPT1040-R68M1	0.68	22.0	39.0	2.4	2.7
MPT1040-R88M1	0.88	20.0	38.0	2.7	3.0
MPT1040-1R0M1	1.0	18.0	36.0	3.0	3.3
MPT1040-1R5M1	1.5	16.0	33.0	3.8	4.2
MPT1040-2R2M1	2.2	12.0	27.0	6.7	7.0
MPT1040-3R3M1	3.3	10.0	18.7	10.8	11.8
MPT1040-4R7M1	4.7	9.5	17.0	15.0	16.5
MPT1040-5R6M1	5.6	8.5	16.0	17.6	19.3

NOTES:

- (1) All test data is referenced to 25°C ambient.
- (2) Ir is the DC current which cause the surface temperature of the part increase approximate 40°C
- (3) Isat is the DC current which cause the inductance drop approximate 20% of Lo.
- (4) Operating temperature range -55°C to 125°C. (The part temperature should be kepted under 125°C when the worse operating condition apply on it. Circuit design, component placement, PWB tracesize and thickness, airflow and other cooling provision may affect the part temperature. Part temperature should be verified in the end application.)
- (5) The rated current is depended on Ir and Isat which one is lower.