

HIGH TEMPERATURE

Shielded Power Inductors – MSS7341T



- Designed for high ambient temperatures – up to 125°C
- AEC-Q200 Grade 1 qualified
- Low DCR and excellent current handling

Core material Ferrite**Core and winding loss** See www.coilcraft.com/coreloss**Environment** RoHS compliant**Terminations** RoHS compliant matte tin over nickel over phos bronze. Other terminations available at additional cost.**Weight:** 0.61 – 0.67 g**Ambient temperature** –40°C to +125°C with (40°C rise) Irms current.**Maximum part temperature** +165°C (ambient + temp rise). **Derating.****Storage temperature** Component: –40°C to +165°C.

Tape and reel packaging: –40°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)**Failures in Time (FIT) / Mean Time Between Failures (MTBF)**

38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332

Packaging 300/7 reel; 1200/13" reel; Plastic tape: 16 mm wide, 0.35 mm thick, 12 mm pocket spacing, 4.5 mm pocket depth**PCB washing** Tested to MIL-STD-202 Method 215 plus an additional aqueous wash. See [Doc787_PCB_Washing.pdf](#).

Part number ¹	Inductance ² (μH)	Percent tolerance ³	DCR (Ohms)		SRF typ ⁴ (MHz)	Isat (A) ⁵			Irms (A) ⁶	
			typ	max		10% drop	20% drop	30% drop	20°C rise	40°C rise
MSS7341T-332_L_	3.3	30 ,20	0.014	0.018	85	2.8	3.4	3.7	3.95	5.00
MSS7341T-502_L_	5.0	30 ,20	0.018	0.023	49	2.4	2.8	3.1	3.40	4.70
MSS7341T-622_L_	6.2	30 ,20	0.024	0.027	42	2.1	2.5	2.7	3.05	4.30
MSS7341T-742_L_	7.4	30 ,20	0.027	0.031	35	2.0	2.3	2.6	2.80	4.10
MSS7341T-872_L_	8.7	30 ,20	0.029	0.034	33	1.8	2.1	2.3	2.80	3.90
MSS7341T-103ML_	10	20	0.032	0.038	32	1.7	2.0	2.2	2.80	3.80
MSS7341T-123ML_	12	20	0.040	0.050	27	1.6	1.8	2.0	2.45	3.30
MSS7341T-153ML_	15	20	0.047	0.055	26	1.4	1.7	1.8	2.05	3.00
MSS7341T-183ML_	18	20	0.065	0.075	25	1.3	1.5	1.6	1.85	2.65
MSS7341T-223ML_	22	20	0.074	0.082	22	1.2	1.4	1.5	1.70	2.35
MSS7341T-273ML_	27	20	0.091	0.109	19	1.0	1.2	1.3	1.50	2.10
MSS7341T-333ML_	33	20	0.104	0.124	17	0.94	1.1	1.2	1.50	1.95
MSS7341T-393ML_	39	20	0.115	0.130	15	0.86	1.0	1.1	1.50	1.90
MSS7341T-473ML_	47	20	0.127	0.155	14	0.80	0.95	1.0	1.50	1.85
MSS7341T-563ML_	56	20	0.174	0.202	11	0.72	0.86	0.94	1.25	1.60
MSS7341T-683ML_	68	20	0.236	0.250	9.6	0.64	0.76	0.83	1.00	1.35
MSS7341T-823ML_	82	20	0.257	0.290	8.5	0.57	0.68	0.74	1.00	1.25
MSS7341T-104ML_	100	20	0.286	0.310	7.2	0.54	0.64	0.70	0.90	1.15
MSS7341T-154ML_	150	20	0.438	0.475	6.0	0.45	0.53	0.58	0.86	1.14
MSS7341T-224ML_	220	20	0.660	0.710	5.0	0.39	0.47	0.51	0.57	0.78
MSS7341T-474KL_	470	10	1.21	1.45	3.0	0.27	0.32	0.35	0.43	0.57
MSS7341T-684KL_	680	10	1.85	1.98	2.5	0.20	0.25	0.27	0.42	0.56

1. When ordering, specify **tolerance**, **termination** and **packaging** codes:**MSS7341T-872NLD****Tolerance:** M = 20%, N = 30% (Table shows stock tolerances in bold.)**Termination:** L = RoHS compliant matte tin over nickel over phos bronze.
Special order: T = RoHS tin-silver-copper (95.5/4/0.5) over gold over nickel over phos bronze or
S = non-RoHS tin-lead (63/37) over gold over nickel over phos bronze.**Packaging:** D = 13" machine-ready reel. EIA-481 embossed plastic tape (1200 parts per full reel).

C = 7" machine-ready reel. EIA-481 embossed plastic tape. Special order (300 parts per full reel).

B = Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter D instead.

2. Inductance measured at 100 kHz, 0.1 Vrms, 0 Adc using a Coilcraft SMD-A fixture in an Agilent/HP 4263B LCR meter.

3. Tolerances shown in bold are stocked for immediate shipment.

4. SRF measured using an Agilent/HP 8753D network analyzer and a Coilcraft SMD-D test fixture.

5. DC current at 25°C that causes the specified inductance drop from its value without current. [Click for temperature derating information.](#)6. Current that causes the specified temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings. [Click for temperature derating information.](#)

7. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.

www.coilcraft.com**US** +1-847-639-6400 sales@coilcraft.com**UK** +44-1236-730595 sales@coilcraft-europe.com**Taiwan** +886-2-2264 3646 sales@coilcraft.com.tw**China** +86-21-6218 8074 sales@coilcraft.com.cn**Singapore** +65-6484 8412 sales@coilcraft.com.sg

Document 725-1 Revised 02/09/17


© Coilcraft Inc. 2017

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.



HIGH TEMPERATURE

High Temperature Power Inductors – MSS7341T Series



Typical L vs Current




Typical L vs Frequency



*Dimensions are of the case not including the termination. For maximum overall dimensions including the termination, add 0.02 in / 0,51 mm.



Recommended Land Pattern



Dimensions are in $\frac{\text{inches}}{\text{mm}}$



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 725-2 Revised 02/09/17

© Coilcraft Inc. 2017

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Coilcraft:

[MSS7341T-622NLB](#) [MSS7341T-153MLD](#) [MSS7341T-332NLB](#) [MSS7341T-332NLD](#) [MSS7341T-742NLB](#)
[MSS7341T-684KLB](#) [MSS7341T-273MLB](#) [MSS7341T-683MLD](#) [MSS7341T-183MLD](#) [MSS7341T-104MLD](#) [MSS7341T-103MLD](#) [MSS7341T-333MLD](#) [MSS7341T-393MLD](#) [MSS7341T-183MLB](#) [MSS7341T-563MLB](#) [MSS7341T-224MLB](#)
[MSS7341T-123MLB](#) [MSS7341T-473MLD](#) [MSS7341T-823MLB](#) [MSS7341T-223MLD](#) [MSS7341T-563MLD](#)
[MSS7341T-223MLB](#) [MSS7341T-123MLD](#) [MSS7341T-224MLD](#) [MSS7341T-823MLD](#) [MSS7341T-872NLD](#)
[MSS7341T-502NLD](#) [MSS7341T-474KLD](#) [MSS7341T-473MLB](#) [MSS7341T-273MLD](#) [MSS7341T-153MLB](#) [MSS7341T-683MLB](#) [MSS7341T-622NLD](#) [MSS7341T-104MLB](#) [MSS7341T-742NLD](#) [MSS7341T-684KLD](#) [MSS7341T-474KLB](#)
[MSS7341T-393MLB](#) [MSS7341T-872NLB](#) [MSS7341T-333MLB](#) [MSS7341T-502NLB](#) [MSS7341T-103MLB](#)