

ADAM TECH MODULAR TELEPHONE PLUGS

MTP SERIES

INTRODUCTION:

ADAM TECHNOLOGIES

Adam Tech MTP series Modular Telephone Plugs are manufactured to terminate flat oval or round telephone cord to REA and Cat. 5 EIA/TIA specifications. Our double strain relief design, molded in polycarbonate, is manufactured with contacts pre-loaded in a variety of sizes and options including shielding and specific contacts for flat or round cable. Adam Tech is a major supplier of telephone line cords to the telecommunications industry.

FEATURES:

Preassembled Contacts REA Compliant Terminations Cat. 5 and 5E available Contacts for Flat of Round wire Short or Long body choices Shielded versions

MATING TELEPHONE JACKS:

Adam Tech modular telephone jack series and all industry standard telephone Jacks.

SPECIFICATIONS:

Material:

Insulator: Polycarbonate, rated UL94V-0

Insulator Color: Clear Contacts: Phosphor Bronze

Contact Plating:

50 µin Gold (optional 15 or 30 µin) over nickel underplate.

Electrical:

Operating voltage: 150V AC max. Current rating: 1.5 Amps max. Contact resistance: 20 m Ω max. initial Insulation resistance: 500 M Ω min.

Dielectric withstanding voltage: 1000V AC for 1 minute

Mechanical:

Cable to plug tensile strength: 7.71 Kgs (17 lbs) min.

Durability: 250 Cycles min. Wire range: 26 to 28 Awg **Temperature Rating:**

Operating temperature: -40°C to +70°C

PACKAGING:

Anti-ESD plastic bags


SAFETY AGENCY APPROVALS:

UL Recognized File No. E224053





ORDERING INFORMATION







OPTIONS:

Add designator(s) to end of part number

= Molded in key (Plug size 8 or 10 only)

= Solid wire contacts

EMI = Metal shielded type (Plug size 8 or 10 only)

OL = Offset Latch (Plug size 6 only)





ADAM TECHNOLOGIES

ADAM TECH MODULAR TELEPHONE PLUGS


MTP SERIES

4P4C PLUG .197 [5.0] 10 [2.52] .260 [6.60] .022 .525 [13.34] [0.56].300 [7.62]






Contact Options



Cable Options



Plug with Metal EMI Shield Option

