NAC3MX-W - Neutrik Page 1 of 2

NAC3MX-W

Locking male cable connector, screw terminals

The powerCON TRUE1 is a locking waterproof 16/20 A true mains connector. It replaces appliance couplers wherever a very rugged solution in combination with a locking device is needed in order to guarantee a safe power connection.

The powerCON TRUE1 is a connector with breaking capacity (CBC), i.e. it can be connected or disconnected under load or live.

Features & Benefits

- True mains connector with breaking capacity (CBC)
- · Lockable 16 A single phase connector (USA: 20 A)
- · Dust and water resistant according to IP65 in mated condition
- · Easy and reliable twist lock system
- · Extremely robust and reliable
- · Unique Neutrik cable retention
- ENEC certified according to IEC 60320
- UL recognized components

Image gallery





Technical Information hide

Р	roc	liid	nt:
	100	ıuı	νL

Title NAC3MX-W

Electrical

 Contact resistance
 ≤ 3 mΩ (inner)

 Dielectric strength
 4 kVdc / 2.8 kVac

 Insulation resistance
 0,1 GΩ (after damp heat test IEC 68-2-30)

 Number of electronical contacts
 2 + PE

 Rated current per contact
 16 A rms (USA: 20 A)

 Rated voltage
 250 V ac

Mechanical

 Cable O.D.
 6 - 12 mm

 Lifetime
 > 5000 mating cycles

 Wiresize
 1.0 - 2.5 mm²

 Wiresize
 12 AWG

Material

 Contact plating
 2 μm Ag

 Contacts
 CuNi1Si0.2

 Insert
 Polyamide (PA 6.6 30 % GR)

 Locking element
 ZuAl4Cu1

Shell	Polyamide (PA 6.6 30 % GR)	
Strain relief	Polyacetal (POM)	
Environmental		
Flammability	UL 94 V-0	
Protection class	IP 65 (mated)	
Temperature range	-30 °C - +80 °C	