# 3M<sup>™</sup> Heel Grounder — Non-Marking NS-HGC1M

## Non-Marking Blue Heel Grounder

The blue sole eliminates scuff marks on ESD floors. The reversible, double life sole is static Elastic Velcro™ provides a secure, comfortable fit. Made in the USA, this quality grounder is tested for electrical performance and is lot numbered. 3M uses time-tested construction techniques including computer controlled stitching, riveting, die cutting and heat cutting to ensure consistent performance.

#### **Standards**

Meets the requirements of ANSI/ESD S-20.20, EIA 625, MIL-STD-1686 and MIL-HDBK-263.

### **Specifications**

Resistor: 1 megohm

Sole: 2-layer, dissipative, blue/black

Ribbon: Gray, multi-strand, carbon

suffused nylon on polyester, sewn in sinusoidal pattern to

provide side-to-side conductivity.

Hook and Loop: 3/4", elastic loop, black

Traceability: Lot coded

Sole Exterior: <10<sup>8</sup> ohms

Total Grounder: 10<sup>7</sup> -10<sup>8</sup> ohm

#### **Part Numbers**

#NS-HGC1M Blue Non-Marking

Heel Grounder, 1 meg resistor See 3M Data Sheets for these

related items:

3M™ Foot Grounder Tester

3M™ Floor Mats



#### **How Foot Grounders Work**

Foot grounders discharge static from a person to ground by connecting the person to a grounded walking surface. A conductive ribbon placed inside the wearer's shoe or sock makes electrical contact with the skin through perspiration. The ribbon is joined to a resistor which limits should accidental exposure to electricity occur. The other end of the resistor is joined to a conductive sole. This sole contacts a grounded ESD floor mat or ESD flooring system. Foot grounders must be worn on both feet to maintain ground contact while walking.

Velcro is a trademark of Velcro Industries.

PRODUCT DATA SHEET

### Foot Grounder - Non-Marking

**PRODUCT** 

BLUE NON-MARKING HEEL GROUNDER

ITEM NUMBER

SEE ABOVE

DATASHEET

1129-A

3M Electronic Solutions Division 6801 River Place Blvd. Austin, TX 78726-9000 US and Canada: 866-722-3736 Fax: 866-722-3735

Fax: 866-722-3735 Intl: 919-718-0000; Fax: 919-774-8174

email: 3Mstaticinfo@mmm.com; www.3Mstatic.com © 2009

3M is a trademark of 3M Company. All other trademarks herein are the property of their respective owners.

