

DASH NO	CABLES ACCOMMODATED	A DIM	B DIM	C FLATS	D FLATS	E DIA	ASSEMBLE PER
-7	TRC-50-2 TRC-75-2	1.135	.096	.438	.438	.500	TAI-189
-8	8227,BELDEN	1.716	.130	.625	.688	.750	TAI-103
-9	TWC-78-2 TWC-124-2	1.135	.096	.438	.438	.500	TAI-102
-A9	BL782,TIMES BL982,TIMES BL1242,TIMES			△	△		
-10	RG-22 754E,AT&T			.625	.688	.750	TAI-103
-11	760A,AT&T						TAI-128
-12	16 PEVL,AT&T V1-AL,GENERAL						TAI-129
-13	TRF-59,TIMES						TAI-165
-13A	8232,BELDEN						TAI-129
-14	8233,BELDEN						TAI-189
-23	250-3884,MICRODOT						TAI-102
-24	202-3934,MICRODOT						TAI-189
-24A	9530A5117,RAYCHEM						TAI-102
-25	T-43M,GENERAL						TAI-189
-25A	5021H5331,RAYCHEM	1.135	.096	.438	.438	.500	TAI-102
-26	7028A5518,RAYCHEM						
-27	T19TPSJ2619EN,WOVEN 202-3927,MICRODOT 202-3942,MICRODOT						
-29	TWC-78-1/TWC-124-1A						
-30	761A,AT&T 8441,BELDEN						TAI-189
-32	TRC-50-1						
-33	TRC-75-1						
-42	21-204,ESSEX 4463,CONSOLIDATED						
-43	250-4044/250-4045 293-3930,MICRODOT						TAI-102
-45	M27500-22TE2T14 1100-66F,STANDARD						TAI-103
-46	9860,BELDEN	1.716	.130	.625	.688	.750	TAI-102
-47	M17/176-00002	1.135	.096	.438	.438	.500	
-49	TWAC-78-1F2	1.716	.130	.625	.688	.750	
-54	89207,BELDEN	1.135	.096	.438	.438	.500	TAI-189
-55	89272,BELDEN						TAI-102
-56	GC875GC1,GRUMMAN						TAI-189
-57	GC875GB1,GRUMMAN						
-58	GC875TM24H,GRUMMAN						
-59	GC875LN1,GRUMMAN						TAI-189
-60	M17/177,THERMATICS 380-10045,BOEING						
-64	7528A5314,RAYCHEM						

FIG 1 △
-9 SHOWN






FIG 2
-9 SHOWN



RED INDICATES ORIGINAL

DATA CONTAINED IN THIS DOCUMENT IS
PROPRIETARY TO TROMPETER ELECTRONICS INC.
AND SHALL NOT BE DISCLOSED, COPIED OR USED
FOR PROCUREMENT OR MANUFACTURE WITHOUT
EXPRESS WRITTEN PERMISSION OF TROMPETER
ELECTRONICS INC.

REVISIONS		310-0025	SH 1
REV	DESCRIPTION	DATE	APPROVED
U	REVISED PER ECD 14778	11-5-02	RAM

CABLE ENTRY			
DASH NO	DIA	DASH NO	DIA
-7	.274	-29	.191
-8	.345	-30	.235
-9	.285	-32	.191
-A9		-33	.217
-10	.455	-42	.300
-11	.347	-43	.200
-12	.485	-45	.183
-13	.362	-46	.475
-13A	.352	-47	.164
-14	.490	-49	.132
-23	.183	-54	.323
-24	.191	-55	.250
-24A	.200	-56	.191
-25	.285	-57	
-25A		-58	.198
-26	.191	-59	
-27	.145	-60	.217
		-64	.183

6. EXAMPLE OF A COMPLETE MODEL NO.

PL74 -47 △

BASIC MODEL NO. DASH NO.

△ IF BEND RELIEF SPRING REQD (SEE FIG 1)
ADD SUFFIX "BR" TO MODEL NO
(NOT AVAILABLE WITH CABLE GROUPS -8,-10,-11,
-12,-13,-13A,-14,-46 & -54)

△ CLAMP NUT OMITTED

△ 2-LUG BAYONET CONCENTRIC TWINAX/TRIAX TRB CABLE PLUG

2. FINISH: TFS-1A (NICKEL)

1. ALL DIM ARE IN INCHES

TYPE △	DASH NO/CABLE GROUP															
TWINAX	-8	-9	-A9	-10	-11	-12	-24	-25	-27	-29	-30	-45	-46	-47	-49	-54
TRIAx	-7	-13	-13A	-14	-23	-24A	-25A	-26	-32	-33	-42	-43	-56	-57	-59	-60
QUADRAx	-58															

INTERPRET DRAWING PER
MIL-STD-100
DIMENSIONS ARE IN INCHES
AND INCLUDE FINISH THICKNESS
UNLESS OTHERWISE SPECIFIED

DRAWN
AAH

DATE
11-4-02

CHECKED
SD

QUALITY
2/11

DATE
11-5-02

DATE
11-5-02

DATE
11-5-02

DATE
11-5-02

DATE
11-5-02

DATE
11-5-02

DATE
11-5-02

DATE
11-5-02

DATE
11-5-02

DATE
11-5-02

DATE
11-5-02

TOL: UNLESS SPECIFIED
.XX
.XXX ±.005
.XXXX
ANGLES

MATERIAL:

FINISH:

DO NOT SCALE DWG

SCALE

SCALE

SCALE

SCALE

SCALE

SCALE

SCALE

SCALE

SCALE

SCALE

SCALE

SCALE

TROMPETER
RF connectivity
a cinch connectivity solutions brand

TITLE:

PL74/PL74BR

SIZE CAGE CODE DRAWING NO. REV.

B 14949 310-0025 U

SCALE NONE DATE: 3/27/78 SHEET 1C

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Cinch Connectivity Solutions:](#)

[PL74-32](#) [PL74-9](#)