





5.00–6.30	28.6–0.1	25.4+0.1
3.00–5.00	28.0–0.1	25.4+0.1
0.75–3.00	27.6–0.1	25.4+0.1
PANEL THICKNESS	X	Y



1571103-2 SHOWN

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN BSV CHK J.MOSIER APVD J.P		07APR04		 Tyco Electronics Corporation Harrisburg, PA 17057	
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME		POWER ROCKER SWITCH, 25.4mm X 27.6mm	
MM		0 PLC ± - 1 PLC ± 0.30 2 PLC ± 0.05 3 PLC ± - 4 PLC ± - ANGLES ± -		PRODUCT SPEC		PANEL CUT-OUT SIZE, DOUBLE POLE, SINGLE THROW	
				NOT APPLICABLE		FOUR TERMINALS, NON-ILLUMINATED	
APPLICATION SPEC		NOT APPLICABLE		SIZE		RESTRICTED TO	
MATERIAL		FINISH		WEIGHT		CAGE CODE	
				-		DRAWING NO	
				A2		00779	
				C-1571103		REV	
				CUSTOMER DRAWING		SCALE 2:1	
						SHEET 1 OF 2	
						REV F1	

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT

BY TYCO ELECTRONICS CORPORATION.

ALL RIGHTS RESERVED.

LOC

DIST

AD00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	—	SEE SHEET 1	—	—	—

LEGACY PART NUMBER

X₁X₂

X₃

X₄

X₅X₆

—

X₇X₈

X₉

—

X₁₀

X₁₁

X₁₂

X₁₃

X₁₄

SWITCH TYPE: X₁X₂ = PR — POWER ROCKER

SECONDARY ROCKER COLOR: X₁₂ = Ø — NOT APPLICABLE

NOMINAL PANEL CUT OUT SIZE: X₃ = D — 25.4x27.6

NUMBER OF POLES: X₄ = D — DOUBLE

SWITCH FUNCTION: X₅X₆ = A1 — ON–OFF, WITH OPAQUE, SINGLE–COLOR ROCKER BUTTON.

LEGEND TEXT PATTERN: X₁₃ =

CURRENT RATING: X₇X₈ = 16 —

TERMINAL TYPE: X₉ = E — QC TAB

FRAME COLOR: X₁₀ = B — BLACK
W — WHITE

ROCKER COLOR: X₁₁ = B — BLACK
G — GREEN
R — RED
W — WHITE

Ø

A

B

C

H

•

○ —

○ |

OFF ON

LEGEND TEXT COLOR: X₁₄ = Ø —NOT APPLICABLE
G — GREEN
R — RED
B — BLACK
W — WHITE

1

MATERIALS:

ROCKER BUTTON & HOUSING: NYLON 66, UL 94 V–2.

TERMINAL, ACTIVE CONTACTOR: COPPER ALLOY PER ASTM B152/B152M

PLUNGER: COPPER ALLOY PER ASTM B036

SPRING: STEEL WIRE PER ASTM A228/A228M

CONTACT: SILVER–TIN OXIDE

2

FINISH:

TERMINAL, ACTIVE CONTACTOR: 1.0µm MIN SILVER

PLUNGER: 3.0µm MIN NICKEL

3

ELECTRICAL SPECIFICATIONS:

CURRENT & VOLTAGE

CONTACT RESISTANCE (INITIAL): <50mΩ

DIELECTRIC STRENGTH (INITIAL): >1000 VAC, 1 MINUTE

INSULATION RESISTANCE (INITIAL): >100MΩ MIN (500VDC BETWEEN OPEN CONTACTS)

INRUSH CURRENT: 50A / 3msec (CAPACITIVE LOAD)

ELECTRICAL LIFE ENDURANCE: >6000 OPERATIONS,

TEMPERATURE RISE AT TERMINALS: <30°C, 6000 OPERATIONS

(AMBIENT CONDITIONS: 25±2°C AND 65±5%R.H)

4

MECHANICAL SPECIFICATIONS:

ACTUATING FORCE: 850g MIN, 1250g MAX

OPERATING LIFE ENDURANCE: >100,000 OPERATIONS

TERMINAL STRENGTH : >10.0kg– QC TAB

5

ENVIRONMENTAL SPECIFICATIONS:

AMBIENT TEMPERATURE: –20°C TO +85°C

HUMIDITY: MAX 85%

SALT SPRAY: NO REMAKABLE RUST IN METAL PARTS (5%SALT / 35°C 24HRS)

SHOCK: NO MECHANICAL DEFECT OR DAMAGE (100g / 10MSEC/ X,Y,Z 3 TIMES)

VIBRATION: NO MECHANICAL DEFECT OR DAMAGE (10–55Hz /1.5mm/ X,Y,Z 2HRS)

6

UL: 16A@125VAC 1/3HP / 10A@250VAC 1/2HP

ENEC: 10(4)A 250V~

7

ELECTRICAL RATINGS, APPROVED AGENCY LOGOS, TERMINAL IDENTIFICATION NUMBERS, AND THE TYCO/ELECTRONICS LOGO MOLDED APPROXIMATELY AS SHOWN ON THE SIDES OF THE SWITCH HOUSING.

8

COMPONENT RECOGNIZED TO US & CANDIAN STANDARDS.

UL FILE NO. E46765

9

COMPONENT–RECOGNIZED TO EUROPEAN STANDARDS

(ENEC & VDE) MARKS LICENSE NO 40020317

10

ROHS 2002/95/EC COMPLIANT

11

TYCO ELECTRONICS LOGO LOCATED APPROXIMATELY AS SHOWN

PRDDA1–16F–BR0HW	5–1571103–6
PRDDA1–16F–BR000	5–1571103–4
PRDDA1–16F–BB0HW	1571103–5
PRDDA1–16F–BB0CW	1571103–3
PRDDA1–16F–BB0BW	1571103–2
PRDDA1–16F–BB000	1571103–1
LEGACY PART NUMBER	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: MM

MATERIAL

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± –
1 PLC ± 0.30
2 PLC ± 0.05
3 PLC ± –
4 PLC ± –
ANGLES ± –
FINISH

DWN BSV 07APR04

CHK J.MOSIER

APVD JP

PRODUCT SPEC

APPLICATION SPEC

WEIGHT –

CUSTOMER DRAWING

Tyco Electronics

Tyco Electronics Corporation

Harrisburg, PA 17057

NAME

POWER ROCKER SWITCH, 25.4mm X 27.6mm

PANEL CUT–OUT SIZE, DOUBLE POLE, SINGLE THROW

FOUR TERMINALS, NON–ILLUMINATED

SIZE

A2

CAGE CODE

00779

DRAWING NO

C=1571103

RESTRICTED TO

–

SCALE

1:1

SHEET

2

OF

2

REV

F1

AMP 1471–9 REV 31MAR2000

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[PRDDA1-16F-BB000](#)