



Solid State Relays Selection Guide

NUMBERING SYSTEM



CLASSIFICATION CHART



ELECTRICAL CHARACTERISTICS

6 Pin DIP (1 Form A/1 Form B)

Type Number	R _{on} (Ω)	V _L (V)	I _L (mA)	P _T (mW)	Viso (V)	T _{OPT} (°C)	T _{STG} (°C)	t _{ON} (ms)	t _{OFF} (ms)	Current Limit
PS710A-1A	0.2	60	1,800	610	1500	-40 to 85	-40 to 100	3.0	1.0	120
PS710B-1A	0.1	60	2,500	675	1500	-40 to 85	-40 to 100	5.0	1.0	
PS7112-1A	6	100	200	610	1500	-40 to 80	-40 to 100	0.4	0.2	
PS7113-1A	2.5	100	350	610	1500	-40 to 80	-40 to 100	3.0	0.2	
PS7122-1A	5	200	200	610	1500	-40 to 80	-40 to 100	2.0	0.2	
PS7122A-1A	8.0	250	200	610	1500	-40 to 80	-40 to 100	1.5	0.2	
PS7141-1A	30	400	150	610	1500	-40 to 80	-40 to 100	1.0	0.2	
PS7141-1B	30	400	150	610	1500	-40 to 80	-40 to 100	0.2	1.0	
PS7142-1A	10	400	200	610	1500	-40 to 80	-40 to 100	5.0	0.2	
PS7142-1B	12	400	200	610	1500	-40 to 80	-40 to 100	0.2	5.0	
PS7160-1A	50	600	90	610	1500	-40 to 80	-40 to 100	1.5	0.2	
PS7341-1A	30	400	150	610	3750	-40 to 85	-40 to 125	1.0	0.2	
PS7341C-1A	35	400	120	610	3750	-40 to 85	-40 to 125	1.0	1.0	
PS7341-1B	30	400	150	610	3750	-40 to 85	-40 to 125	0.03	0.6	
PS7341A-1B	26	400	120	610	3750	-40 to 85	-40 to 125	0.2	1.5	
PS7342-1A	10	400	200	610	3750	-40 to 85	-40 to 125	2.5	0.2	
PS7360-1A	50	600	90	610	3750	-40 to 85	-40 to 125	2.0	0.2	
PS7522-1A	5	200	200	1500	1500	-40 to 80	-40 to 100	12.0	6.5	

4 Pin SOP (1 Form A/1 Form B)

Type Number	R _{on} (Ω)	V _L (V)	I _L (mA)	P _T (mW)	Viso (V)	T _{OPT} (°C)	T _{STG} (°C)	t _{ON} (ms)	t _{OFF} (ms)	Current Limit
PS7200A-1A	12	40	100	150	1500	-40 to 80	-40 to 100	0.5	0.2	210
PS7200B-1A	1.5	40	250	150	1500	-40 to 80	-40 to 100	1.0	0.2	
PS7200H-1A	3.5	40	160	150	1500	-40 to 80	-40 to 100	0.5	1.0	
PS7200K-1A	2.0	40	200	150	1500	-40 to 80	-40 to 100	1.0	1.0	
PS7200R-1A	12.5	40	120	150	1500	-40 to 80	-40 to 100	0.5	1.0	
PS7206-1A	0.8	60	600	350	1500	-40 to 85	-40 to 100	2.0	0.5	
PS7212-1A	6.0	100	200	350	1500	-40 to 80	-40 to 100	1.0	0.2	
PS7214-1A	1.2	100	400	350	1500	-40 to 85	-40 to 100	2.0	1.0	
PS7241-1A	30	400	120	350	1500	-40 to 80	-40 to 100	2.0	0.2	
PS7241-1B	35	400	120	350	1500	-40 to 80	-40 to 100	0.2	2.0	
PS7241C-1A	35	400	120	350	1500	-40 to 80	-40 to 100	2.0	0.2	

8 Pin DIP (2 Form A/2 Form B, Dual 1 Form A/1 Form B)

Type Number	R _{on} (Ω)	V _L (V)	I _L (mA)	P _T (mW)	Viso (V)	T _{OPT} (°C)	T _{STG} (°C)	t _{ON} (ms)	t _{OFF} (ms)	Current Limit
PS7111-2A	6.0	100	100	850	1500	-40 to +80	-40 to +100	0.4	0.2	
PS7113-2A	2.5	100	350	850	1500	-40 to 80	-40 to 100	3.0	0.2	
PS7122-2A	5.0	200	200	850	1500	-40 to 80	-40 to 100	2.0	0.2	
PS7122A-2A	8.0	250	200	850	1500	-40 to 80	-40 to 100	1.5	0.2	
PS7122A-1C	8.0	250	200	850	1500	-40 to 80	-40 to 100	1.5	0.2	
PS7141-2A	30	400	150	850	1500	-40 to 80	-40 to 100	1.0	0.2	
PS7141-2B	30	400	150	850	1500	-40 to 80	-40 to 100	0.2	1.0	
PS7141-1C	30	400	150	850	1500	-40 to 80	-40 to 100	1.0	0.2	
PS7141C-2A	35	400	120	850	1500	-40 to 80	-40 to 100	2.0	1.0	
PS7142-2B	12	400	200	850	1500	-40 to 80	-40 to 100	0.2	2.0	
PS7142-1C	12	400	200	850	1500	-40 to 80	-40 to 100	2.0	0.2	
PS7142-2A	12	400	200	850	1500	-40 to 80	-40 to 100	2.0	0.2	
PS7160-2A	50	600	90	850	1500	-40 to 80	-40 to 100	1.5	0.2	
PS7522-2A	5.0	200	200	850	1500	-40 to 80	-40 to 100	12	6.5	

ELECTRICAL CHARACTERISTICS *continued*


8 Pin SOP (2 Form A/2 Form B, Dual 1 Form A/1 Form B)

Type Number	R _{on} (Ω)	V _L (V)	I _L (mA)	P _T (mW)	V _{iso} (V)	T _{OPT} (°C)	T _{STG} (°C)	t _{on} (ms)	t _{off} (ms)	Current Limit
PS7211-2A	6.0	100	100	460	1500	-40 to 80	-40 to 100	1.0	0.2	
PS7221-2A	10.0	260	170	460	1500	-40 to 80	-40 to 100	1.0	0.2	
PS7221A-2A	10	260	170	460	1500	-40 to 80	-40 to 100	1.0	0.2	
PS7241-2A	30	400	120	460	1500	-40 to 80	-40 to 100	1.0	0.2	
PS7241-2B	30	400	120	460	1500	-40 to 80	-40 to 100	0.2	1.0	
PS7241-1C	30	400	120	460	1500	-40 to 80	-40 to 100	1.0	0.2	

8 Pin SOP (Hybrid, Optocoupler & SSR)


Type Number	R _{on} (Ω)	V _L (V)	I _L (mA)	P _T (mW)	V _{iso} (V)	T _{OPT} (°C)	T _{STG} (°C)	t _{on} (ms)	t _{off} (ms)	Current Limit
PS7241-AT1	30	400	120	630	1500	-40 to 80	-40 to 100	1.0	0.2	
PS7241-AT5	30	400	120	630	1500	-40 to 80	-40 to 100	1.0	0.2	

PIN CONNECTIONS




1 Form A/1 Form B

Available in 6 pin DIP




2 Form A/2 Form B, Dual 1 Form A/1 Form B

All available in 8 pin SOP & DIP packages



DC Hybrid: Optocoupler plus SSR

1 Form A in 8 pin SOP



AC Hybrid: Optocoupler plus SSR

1 Form A in 8 pin SOP

STANDARD

	Standard	Lead Bending	Taping Option
6 Pin DIP 1 Form A/1 Form B	PS710A-1A PS710B-1A PS7113-1A PS7122-1A PS7122A-1A PS7141-1A PS7141-1B PS7142-1A PS7142-1B PS7160-1A PS7341A-1B	PS710AL-1A PS710BL-1A PS7113L-1A PS7122L-1A PS7122AL-1A PS7141L-1A PS7141L-1B PS7142L-1A PS7142L-1B PS7160L-1A PS7341AL-1B	PS710AL-1A-E3, E4 PS710BL-1A-E3, E4 PS7113L-1A-E3, E4 PS7122L-1A-E3, E4 PS7122AL-1A-E3, E4 PS7141L-1A-E3, E4 PS7141L-1B-E3, E4 PS7142L-1A-E3, E4 PS7142L-1B-E3, E4 PS7160L-1A-E3, E4 PS7341L-1B-E3, E4
4 Pin SOP 1 Form A/1Form B		PS7200H-1A PS7200K-1A PS7200R-1A PS7206-1A PS7212-1A PS7214-1A PS7241-1A PS7241-1B PS7241C-1A	PS7200H-1A-E3, E4, F3, F4 PS7200K-1A-E3, E4, F3, F4 PS7200R-1A-E3, E4, F3, F4 PS7206-1A-E3, E4, F3, F4 PS7212-1A-E3, E4, F3, F4 PS7214-1A-E3, E4, F3, F4 PS7241-1A-E3, E4, F3, F4 PS7241-1B-E3, E4, F3, F4 PS7241C-1A-E3, E4, F3, F4
8 Pin DIP 2 Form A/2 Form B/ 1 Form C	PS7113-2A PS7122-2A PS7122A-2A PS7122A-1C PS7141-2A PS7141-2B PS7141-1C PS7141C-2A PS7142-1C PS7142-2B PS7142-2A PS7160-2A	PS7113L-2A PS7122L-2A PS7122AL-2A PS7122AL-1C PS7141L-2A PS7141L-2B PS7141L-1C PS7141CL-2A PS7142L-1C PS7142L-2B PS7142L-2A PS7160L-2A	PS7113L-2A-E3, E4 PS7122L-2A-E3, E4 PS7122AL-2A-E3, E4 PS7122AL-1C-E3, E4 PS7141L-2A-E3, E4 PS7141L-2B-E3, E4 PS7141L-1C-E3, E4 PS7141CL-2A-E3, E4 PS7142L-1C-E3, E4 PS7142L-2B-E3, E4 PS7142L-2A-E3, E4 PS7160L-2A-E3, E4
8 Pin SOP 2 Form A/2 Form B/ 1 Form C		PS7211-2A PS7221A-2A PS7241-2A PS7241-2B PS7241-1C	PS7211-2A-F3, F4 PS7221A-2A-F3, F4 PS7241-2A-F3, F4 PS7241-2B-F3, F4 PS7241-1C-F3, F4


HIGH ISOLATION VOLTAGE

	Standard	Lead Bending	Taping Option
6 Pin DIP 1 Form A/1 Form B	PS7341-1A PS7341-1B PS7342-1A PS7360-1A	PS7341L-1A PS7341L-1B PS7342L-1A PS7360L-1A	PS7341L-1A-E3, E4 PS7341L-1B-E3, E4 PS7342L-1A-E3, E4 PS7360L-1A-E3, E4


SLOW SWITCHING

	Standard	Lead Bending	Taping Option
6 Pin DIP 1 Form A/1 Form B	PS7522-1A	PS7522L-1A	PS7522L-1A-E3, E4
8 Pin DIP 2 Form A	PS7522-2A	PS7522L-2A	PS7522L-2A-E3, E4

FAST SWITCHING



HIGH FREQUENCY



HYBRID




CURRENT LIMITING




TAPING SPECIFICATIONS (Units in mm)

4 PIN SOP


Outline and Dimensions (Tape)




Taping Direction



Outline and Dimensions (Reel)




Packaging: E3/E4 900 pcs/reel




Packaging: E3/E4 3500 pcs/reel

6, 8 PIN DIP


Outline and Dimensions (Tape)



Taping Direction



Outline and Dimensions (Reel)




Packaging: 1000 pcs/reel


TAPING SPECIFICATIONS (Units in mm) *continued*

8 PIN SOP


Outline and Dimensions (Tape)



Taping Direction




Outline and Dimensions (Reel)




Packaging: 1500 pcs/reel

4 PIN SOP (φ255 Reel)


Outline and Dimensions (Tape)



Taping Direction




Outline and Dimensions (Reel)




Packaging: 1000 pcs/reel

SOLID STATE RELAYS PACKAGE DIAGRAMS (Units in mm)


6 PIN DIP




6 PIN DIP - lead bending type




8 PIN DIP




8 PIN DIP - lead bending type



4 PIN SOP - lead bending type



8 PIN SOP - lead bending type



MARKING



Company & Country Name
Type Number
Assembly Lot

No. 1 pin Mark

N 6 40

Serial Code in Week
Assembly Year
Rank Name

INTERNATIONAL SAFETY STANDARDS

SOLID STATE RELAYS PART NUMBERS				PS71XX-1A PS71XX-2A	PS710A-1A PS710B-1A	PS71XX-1B PS71XX-2B PS71XX-1C	PS72XX-1A	PS72XX-2A	PS7241-AT1 PS7241-AT5	PS73XX-1A PS73XXC-1A PS73XXC-1B	PS75XX-1A PS75XX-2A
PARAMETER (Units: mm) (Minimum Dist.)	Outer Creepage Distance			7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
	Clearance Distance			7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
	Isolation Distance			0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
	Inner Creepage Distance			4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
	Breakdown Voltage			1.5 k	1.5 k	1.5 k	1.5 k	1.5 k	1.5 k	3.75 k	1.5 k
Organization	Country	Standard No	NEC Approval No.								
UL	USA	UL1577	E72422(S)	●	●	●	●	●	●	●	●
CSA	Canada	CL9073X0030	CA101391	⊙	●/⊙	⊙	⊙	●	●	●	●
VDE	Germany	VDE0884	See Right Table	⊙	⊙	⊙	●/⊙	●/⊙	●/⊙	●	●
BSI	UK	BS415 /EC55	7112 (4 pin) 7250 (6 pin)	●	⊙	●	●	●	●	●	●
		BS7002 /EC950	7240 (4 pin) 7615 (6 pin)	●	●/⊙	●	●	●	●	●	●
SEMKO	Sweden	SS-441-01-55	9317144	—	—	—	—	—	—	—	—
		SS-EN-60-950	9317144	—	—	—	—	—	—	—	—
SETI	Finland	E 65-89	167265-08	—	—	—	—	—	—	—	—
		SFS-EN-60-950	167265-08	—	—	—	—	—	—	—	—
NEMKO	Norway	NEK-HD 195 S6	A21409	—	—	—	—	—	—	—	—
		NEK-EN-60-950	A21409	—	—	—	—	—	—	—	—
DEMKO	Denmark	Section 101	300535	—	—	—	—	—	—	—	—
		Section 137	300535	—	—	—	—	—	—	—	—


● Approved

⊙ Under Application

○ Under Planning

— N/A

TYPICAL PART NUMBER



EXCLUSIVE NORTH AMERICAN AGENT FOR NEC RF, MICROWAVE & OPTOELECTRONIC SEMICONDUCTORS



CALIFORNIA EASTERN LABORATORIES • Headquarters • 4590 Patrick Henry Drive • Santa Clara, CA 95054-1817 • (408) 988-3500 • Telex 34-6393 • FAX (408) 988-0279

DATA SUBJECT TO CHANGE WITHOUT NOTICE

Internet: <http://WWW.CEL.COM>

09/06/2001

09/06/2001